



	<a href="#">TV OR MONITOR MOUNT BRATECK-LCD-142A</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE76H0T- ITPF(2.8MM)(C) - 5 Mpx Hikvision</a>
		
	66.00 PLN 66.00 PLN	249.00 PLN 249.00 PLN
Standard	...	AHD / HD-CVI / HD-TVI / CVBS
Sensor	...	Progressive Scan CMOS
Matrix size	...	5 Mpx
Mounting standard	VESA 75, 100, 150, 200, 200x100	...
Screen size range	17 " ... 37 "	...
Bearing capacity	20 kg	...
Distance from mounting surface	70 ... 250 mm from wall	...
Tilt adjustment	-15 ° ... 15 °	...
Horizontal rotation	Articulated arm with two swivels in range -90 ° ... 90 ° each	...
Rotation in the plane of the screen	360 °	...
Resolution	...	<ul style="list-style-type: none"> <li>• 2560 x 1944 - 5 Mpx @ AHD / HD-TVI - 20 fps</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps</li> <li>• 1920 x 1080 - 1080p @ HD-TVI - 25 fps</li> <li>• 960 x 576 - 960H @ PAL</li> </ul>
Range of IR illumination	...	20 m
IR illuminator power adjustment	...	Automatic
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> <li>• 85 ° (manufacturer data)</li> <li>• 83 ° (our tests result)</li> </ul>
IR illuminator support	...	ICR - Movable InfraRed filter
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	...	—

Main features	...	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>
OSD menu	...	OSD menu available via recorder
Power supply	...	12 V DC / 340 mA
Power consumption	...	≤ 4.3 W
Housing	...	Dome, Plastic
Color	Black	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-40 °C ... 60 °C
Weight	1.1 kg	0.15 kg
Dimensions	195 x 119 x (70 ... 250) mm	Ø 85 x 79 mm
Manufacturer / Brand	...	Hikvision
SAP Code	...	300613619
Guarantee	2 years	3 years