




	BUSHING FOR SPIRAL PIPE GUS-32G/P	VIDEO BALUN TR-8H/DC/R19	SET OF UTP / COAXIAL CONVERTERS FOR LAN+POE TRANSMISSION XCOAX4-SET 2 PCS SET ATTE
			
	9.52 PLN 9.52 PLN	255.40 PLN 255.40 PLN	469.00 PLN 469.00 PLN
Connectors	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs cable terminal • 1 pcs BNC
LAN ports	1 pcs RJ45 100 Mbps
Standard	...	<ul style="list-style-type: none"> • AHD - 5 Mpx, • HD-CVI - 8 Mpx 4K UHD, • HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC 	...
Input current	...	2 x max. 10 A	...
Maximal power voltage	...	max. 40 V DC / 28 V AC	...
Max. output current for single output	...	2.5 A	...
Device type	...	Passive	...
Number of channels	...	8 Video + DC	...
Coaxial socket voltage range 75Ω (CVBS)	...	1 Vpp	...
LAN+PoE port configuration description	<ul style="list-style-type: none"> • xCOAX4-SW : PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+"-": 3, 6 pins) or ("+"-": 4, 5 pins; "+"-": 7, 8 pins) • xCOAX4-CAM : Port LAN 10/100Mb or LAN + PoE OUT - PoE (802.3bt) ≤ 60 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W
Video transmission range	...	<ul style="list-style-type: none"> • 250 m @ 720p - UTP cat. 5e • 400 m @ CVBS - PAL / NTSC - UTP cat. 5e 	...
Output voltage	...	max. 40 V	...
Transmission range	<ul style="list-style-type: none"> < 1000 m @ Coaxial cable < 100 m @ xCOAX4-SW - Switch PoE < 100 m @ xCOAX4-CAM - IP Camera

LED indicators	<ul style="list-style-type: none"> • PoE • LAN • Link • 10Mb
Attenuation	...	<ul style="list-style-type: none"> • 4.43 MHz @ 0.09 dB • 11 MHz @ 0.42 dB • 21 MHz @ 1.04 dB • 38 MHz @ 0.85 dB • 42 MHz @ 1.00 dB • 67.5 MHz @ 0.87 dB 	...
Symmetrical socket impedance	...	100 Ω	...
Protections	<ul style="list-style-type: none"> • Overvoltage - LAN, BNC • Short-circuit - xCOAX4-SW
Connectors type	...	<ul style="list-style-type: none"> • Video - 8 x BNC Socket • DC - Cable terminals 	...
Main features	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Watchdog function - Coaxial cable
Symmetrical socket type	...	Cable terminals	...
Housing type	...	RACK 19", 1U	...
Permissible relative humidity	...	< 95 %	...
Power supply	xCOAX4-SW : <ul style="list-style-type: none"> • 10 ... 58 V DC - cable terminal • PoE 802.3af/at / PASSIVE • The output PoE voltage is equal to the input voltage
Power consumption	1.35 W (total)
Housing	Plastic (PC)
"Index of Protection"	IP20
Operation temp	...	-10 °C ... 55 °C	-25 °C ... 65 °C

Power supply distance	...	Power supply 12V DC 353 m @ 50 mA 235 m @ 75 mA 176 m @ 100 mA 141 m @ 125 mA 117 m @ 150 mA 88 m @ 200 mA 70 m @ 250 mA 58 m @ 300 mA 50 m @ 350 mA 44 m @ 400 mA 39 m @ 450 mA 35 m @ 500 mA 29 m @ 600 mA 25 m @ 700 mA 22 m @ 800 mA 19 m @ 900 mA 17 m @ 1000 mA	...
Weight	...	0.4 kg	0.033 kg (single element)
Dimensions	...	483 x 44 x 53 mm	<ul style="list-style-type: none"> • 73 x 52 x 20 mm - xCOAX4-SW • 73 x 52 x 20 mm - xCOAX4-CAM
Guarantee	...	3 years	3 years
Manufacturer / Brand	...	DELTA	ATTE

