

	<a href="#">POWER DISTRIBUTION UNIT ACAR-S8-DUAL</a>	<a href="#">USB 3.0 ETHERNET NETWORK ADAPTER TL-UE306 TP-LINK</a>	<a href="#">IP CAMERA IPC3614LB-SF28K-G - 3.7 Mpx 2.8 mm UNIVIEW</a>
			
	99.56 PLN 99.56 PLN	62.19 PLN 62.19 PLN	510.26 PLN 510.26 PLN
Standard	...	...	TCP/IP
Supported standards	...	Gigabit Ethernet	...
Sensor	...	...	1/3 " Progressive Scan CMOS
Rated voltage	230 V AC / 50 Hz	...	...
Chipset	...	AX88179	...
Matrix size	...	...	4 Mpx
Nominal load current	10 A (total)	...	...
Supported transmission speeds	...	10 / 100 / 1000 Mbps	...
Scanning system	...	...	Progressive
Interface	...	USB 3.0	...
Nominal voltage of surge suppressor	250 V / 50 Hz	...	...
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...	...
Number of outlets	8 grounded outlets 10A/250V	...	...
Automatic delayed fuse	✓	...	...
Ports	...	<ul style="list-style-type: none"> <li>• 1 x RJ45,</li> <li>• 1 x USB 3.0 - A type</li> </ul>	...
Nominal stroke current	2 kA (L/N) - 8/20 μs	...	...
Operating system	...	Windows 7 / 8 / 8.1 / 10, Linux	...
Resolution	...	...	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Maximum stroke current	6.5 kA (L/N) - 8/20 μs	...	...
Lens	...	...	2.8 mm
Response time	< 25 ns	...	...
Certificates	...	CE, FCC	...
View angle	...	...	<ul style="list-style-type: none"> <li>• 97 ° (manufacturer data)</li> <li>• 90 ° (our tests result)</li> </ul>
Switch	two-way, with light indication	...	...
Range of IR illumination	...	...	30 m
Length of the cable	1.4 m	...	...
S/N ratio	...	...	> 52 dB
RS-485 interface	...	...	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Memory card slot	...	...	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	...	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	...	—
Audio	...	...	—
Main stream frame rate	...	...	25 fps @ 3.7 Mpx
Network interface	...	...	10/100 Base-T (RJ-45)
Network protocols	...	...	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL / TLS, SNMP
WEB Server	...	...	Built-in
Max. number of on-line users	...	...	32
ONVIF	...	...	✓
Mobile phones support	...	...	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>
Default IP address	...	...	DHCP or 192.168.1.13
Default admin user / password	...	...	admin / 123456
Web browser access ports	...	...	80, 554
PC client access ports	...	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	...	...	80
Port ONVIF	...	...	80
RTSP URL	...	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream



Main features	...	<ul style="list-style-type: none"> <li>• Compact folding design</li> <li>• Plug &amp; Play</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Motion Detection - max. 4 zones</li> <li>• Privacy zones - max. 4</li> <li>• Sharpness - sharper image outlines</li> </ul>
Power supply	...	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 330 mA</li> </ul>
Power consumption	...	...	≤ 4 W
Housing	Plastic - non-flammable	...	Dome, Metal + Plastic
Color	...	...	White
"Index of Protection"	...	...	IP67
Vandal-proof	...	...	—
Operation temp	...	...	-30 °C ... 60 °C
Weight	0.52 kg	0.03 kg	0.34 kg
Dimensions	445 x 54 x 55 mm	<ul style="list-style-type: none"> <li>• 71 x 26 x 16 mm</li> <li>• Length of the cable : 11 cm</li> </ul>	Ø 118 x 97 mm
Supported languages	...	...	Polish, English
Manufacturer / Brand	...	TP-LINK	UNIVIEW
Guarantee	2 years	2 years	3 years