




|                                      | <a href="#">KEYPAD FOR ALARM CONTROL PANEL PULSON-LCD/C-WH</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <a href="#">POWER DISTRIBUTION UNIT ACAR-504/WF/RACK</a>                          | <a href="#">POWER DISTRIBUTION UNIT ACAR-F5/FA/RACK</a>                             |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |  |  |
|                                      | 232.00 PLN<br>232.00 PLN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 150.96 PLN<br>150.96 PLN                                                          | 112.71 PLN<br>112.71 PLN                                                            |
| Support                              | PulsON Alarm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | ...                                                                               | ...                                                                                 |
| Rated voltage                        | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 230 V AC                                                                          | 230 V AC / 50 Hz                                                                    |
| Rated current                        | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 10 A (total)                                                                      | ...                                                                                 |
| Nominal load current                 | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | ...                                                                               | max. 10 A (total)                                                                   |
| Maximal total load                   | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | ...                                                                               | 2300 W                                                                              |
| Nominal voltage of surge suppressor  | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 250 V / 50 Hz                                                                     | 250 V / 50 Hz                                                                       |
| Protection level of surge suppressor | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | ≤ 1.3 kV (L/N)                                                                    | ≤ 1.3 kV (L/N)                                                                      |
| Automatic delayed fuse               | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | ...                                                                               | 10 A / 250 V                                                                        |
| Leak current                         | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | < 0.5 mA                                                                          | ...                                                                                 |
| Number of outlets                    | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 5 grounded outlets<br>10A/250V                                                    | 5 grounded outlets<br>10A/250V                                                      |
| Nominal stroke current               | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 2.5 kA (L/N) - 8/20 μs                                                            | 2 kA (L/N) - 8/20 μs                                                                |
| Maximum stroke current               | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 6.5 kA (L/N) - 8/20 μs                                                            | 10 kA (L/N) - 8/20 μs 2 type                                                        |
| Main features                        | <ul style="list-style-type: none"> <li>• Large, easy to read LCD graphic display with backlight,</li> <li>• Alarms: keypad hold-down PANIC, FIRE and AUX,</li> <li>• 6 programmable function buttons to control the system,</li> <li>• Zone state signaling - LED diodes,</li> <li>• White button illumination</li> <li>• Buzzer for acoustic signaling of some system events</li> <li>• Microswitch as tamper contact</li> <li>• Additional 2 detection circuits</li> <li>• DIP SWITCH for configuration and addressing</li> <li>• Simple and quick device installation</li> </ul> | ...                                                                               | ...                                                                                 |
| Response time                        | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | < 25 ns                                                                           | < 25 ns                                                                             |
| Switch                               | ...                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | two-way, with light indication                                                    | two-way, with light indication                                                      |

|                           |                         |                                       |                                                                                                                                      |
|---------------------------|-------------------------|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Compliance with standards | EN 50131, Grade 2       | ...                                   | ...                                                                                                                                  |
| Color                     | White                   | ...                                   | ...                                                                                                                                  |
| Power supply              | 12 V DC - Bus connector | ...                                   | ...                                                                                                                                  |
| Main features             | ...                     | ...                                   | <ul style="list-style-type: none"> <li>• Current paths shutters</li> <li>• DC filter to eliminate interferences : ≤ 35 dB</li> </ul> |
| Current consumption       | max. 35 mA              | ...                                   | ...                                                                                                                                  |
| Housing                   | ...                     | RACK 19", 1U, Plastic - non-flammable | RACK 19", 1U, Plastic - non-flammable                                                                                                |
| Operation temp            | -10 °C ... 55 °C        | ...                                   | ...                                                                                                                                  |
| Weight                    | 0.16 kg                 | 0.59 kg                               | 0.93 kg                                                                                                                              |
| Dimensions                | 157 x 95 x 20 mm        | 383 x 58 x 55 mm                      | 484 x 54 x 55 mm                                                                                                                     |
| Length of the cable       | ...                     | 2.7 m                                 | 2.9 m                                                                                                                                |
| Manufacturer / Brand      | PulsON Alarm            | ...                                   | ...                                                                                                                                  |
| Guarantee                 | 2 years                 | 2 years                               | 2 years                                                                                                                              |