



	SWITCH POE RG-S2915-24GT4MS-P-L 24-PORT RUIJIE	EXTENDER RECEIVER HDMI+USB-EX-100/RX SIGNAL
		
	3651.00 PLN 3651.00 PLN	214.20 PLN 214.20 PLN
Device type	...	Receiver
Supported HDMI resolutions	...	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Maximal transmission range	...	100 m UTP cat. 5e, 6
Protocols	...	HdbitT
Main features	...	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • The devices do not require direct connection, they also operate via the LAN network • Audio transmission via network
LAN ports	<ul style="list-style-type: none"> • 24 x RJ45 10/100/1000 Base-T (24 x PoE (802.3af/at)), • 4 x port SFP - Uplink • 1 x RJ45 - Configuration possibility from PC, • 1 x USB - Configuration possibility from PC 	...
Permissible relative humidity	...	20 % ... 90 % (non-condensing)
Management	✓	...
Number of fan coolers	2	...
Transmission speed	<ul style="list-style-type: none"> • 10/100/1000 Mbps : 24 LAN & PoE ports Uplink ports • 100/1000/2500 Mbps - 4 x SFP ports 	...
Maximal total power	370 W	...
Switching capacity	68 Gb/s	...
Forwarding rate	51 Mpps	...
MAC addresses table	16k	...
Mobile phones support	Android: Free application Ruijie Reye iOS (iPhone): Free application Ruijie Reye	...

Main features	<ul style="list-style-type: none"> • Can be mounted in a Rack cabinet • Switch is managed through the web and the cloud (Ruijie Reeye application) • Access Control List - ACL package filtering based on source and destination IP addresses • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • DHCP client • BPDU Filtering/Guard • Loop back detection • Spanning Tree STP/RSTP • Errdisable Recovery • IGMP Snooping V1/V2/V3 • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h 	...
Certificates	CE, RoHS	...
Protections	Protection against lightning discharges : 10 kV	...
Housing	Desktop, Metal	...
Power supply	100 V ... 240 AC	5 V DC / 1 A (power adapter included)
Power consumption	≤ 403 W	...
Operation temp	0 °C ... 45 °C	-10 °C ... 60 °C
Weight	3.04 kg	0.168 kg
Dimensions	442 x 222 x 44 mm	110 x 89 x 26 mm
Manufacturer / Brand	RUIJIE	SIGNAL
Guarantee	3 years	2 years