

	<u>RESIDUAL CURRENT CIRCUIT BREAKER LE-410919 ONE-PHASE, AC TYPE 30 mA 10 A LEGRAND</u>	<u>IP CAMERA APTI-AI401VA3-2812W - 4 Mpx 2.8 ... 12 mm</u>
		
	192.19 PLN 192.19 PLN	286.40 PLN 286.40 PLN
Standard	...	IP
Device type	Residual Current Circuit Breaker, One-phase, AC type, B curve	...
Rated sensitivity	30 mA	...
Rated current	10 A	...
Number of poles	2	...
Breaking capacity	6000 A	...
Rated voltage	230 V AC / 50 Hz	...
Connectors type	screw terminals	...
Resolution	...	2688 x 1512 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	...	1/3 " Progressive Scan CMOS
Main features	• Can be equipped with DX3 series signalling and remote tripping auxiliaries and motorised controls • Provided space for a label with description • Can be connected with using the supply busbars fork-type or prong-type	...
Lens	...	2.8 ... 12 mm
View angle	...	91 ° ... 31 °
Range of IR illumination	...	30 m
Width in 17.5 mm modules	2	...
Memory card slot	...	—
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Main stream frame rate	...	25 fps @ 4 Mpx
Alarm inputs / outputs	...	—
Audio	...	• External microphone input - Cinch socket ,
WEB Server	...	Built-in
Max. number of on-line users	...	10

ONVIF	...	19.12
Mobile phones support	...	Port no.: 6000 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address	...	192.168.1.168
Default admin user / password	...	admin / admin
Web browser access ports	...	80
PC client access ports	...	80
Mobile client access ports	...	6000
Port ONVIF	...	80
RTSP URL	...	rtsp://user:password@ip_address:554/0 - Main stream rtsp://user:password@ip_address:554/1 - Sub stream
Intelligent image analysis	...	• intrusion - motion detection based on human detection
Main features	...	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • Flicker Control - The technology eliminates the tiring eyes flickering image effect • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • ICR - Movable InfraRed filter • Mirror - Mirror image • Motion Detection • Privacy zones - max. 3 • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • RESET button - on the cable
Power supply	...	12 V DC / 350 mA PoE (802.3af)
Power consumption	...	≤ 4.2 W
Housing	Plastic, DIN, TS-35 rail mounting	Dome - Metal
Vandal-proof	...	—
Color	...	White
"Index of Protection"	...	IP67

Operation temp	...	-20 °C ... 60 °C
Weight	0.22 kg	0.58 kg
Dimensions	36 x 83 x 75 mm	Ø 119 x 98 mm
Supported languages	...	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand	LEGRAND	APTI
Guarantee	2 years	2 years

