



	POWER DISTRIBUTION UNIT LE-049490 (4 OUTLETS) 3 m LEGRAND	NVR DS-7732NI-I4 32 CHANNELS Hikvision
		
	71.88 PLN 71.88 PLN	3682.00 PLN 3682.00 PLN
Standard	...	TCP/IP
Rated voltage	230 V AC / 50 Hz	...
Total maximal current	16 A	...
Maximal total load	3680 W	...
Number of outlets	4 grounded outlets 16A/250V CEE 7/5	...
Fuse	—	...
Switch	—	...
Wire gauge	3 x 1.5 mm ²	...
Length of the cable	3 m	...
Housing	Plastic	...
Color	White / Light gray	...
Supported resolutions	...	32 @ 4000 x 3000 px, 32 @ 3840 x 2160 px, 32 @ 3072 x 2048 px, 32 @ 2592 x 1944 px, 32 @ 2560 x 1944 px, 32 @ 2560 x 1440 px, 32 @ 2048 x 1536 px, 32 @ 1920 x 1536 px, 32 @ 1920 x 1080 px, 32 @ 1280 x 720 px, 32 @ 704 x 576 px
Video outputs	...	1 pcs HDMI 1 pcs VGA
Audio support	...	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support
Audio inputs	...	1 pcs Microphone, CINCH
Audio outputs	...	1 pcs CINCH
Image compression method	...	H.265 / H.264 / H.264+ / MPEG-4



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Maximal total frame rate	...	800 fps @ 4000 x 3000 px, 800 fps @ 3840 x 2160 px, 800 fps @ 3072 x 2048 px, 800 fps @ 2592 x 1944 px, 800 fps @ 2560 x 1944 px, 800 fps @ 2560 x 1440 px, 800 fps @ 2048 x 1536 px, 800 fps @ 1920 x 1536 px, 800 fps @ 1920 x 1080 px, 800 fps @ 1280 x 720 px, 800 fps @ 704 x 576 px
Supported hard drives	...	4 x 6 TB SATA
Recording modes	...	Manual, Sensor, Motion detection, Schedule
Network protocols	...	TCP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function Records playback from max. 16 channels in the same time @ 1080p or max. 4 @ 4K
Bitrate	...	max. 256 Mbps
Network functions	...	<ul style="list-style-type: none"> • Live image view, Playback the records, Backup the records • max. 128 on-line users - iVMS-4200 application • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its
ONVIF	...	✓
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) Android: Free application iVMS-4500 or Hik-Connect iOS (iPhone): Free application iVMS-4500 or Hik-Connect
Default IP address	...	DHCP or 192.168.1.64
Default admin user / password	...	admin / -
Web browser access ports	...	80, 8000
PC client access ports	...	8000
Mobile client access ports	...	8000
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs	...	16 / 4
PTZ control	...	✓
Motion Detection	...	22 x 18 motion zones
Intelligent image analysis	...	✓
Mouse support	...	✓

IR remote controller in the set	...	✓
Power supply	...	100 ... 240 V AC
Weight	0.55 kg	4.17 kg
Dimensions	208 x 53 x 37 mm	445 x 390 x 76 mm
Supported languages	...	English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Country of origin	...	China
SAP Code	...	303602967
Manufacturer / Brand	LEGRAND	Hikvision
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00