

	SWITCHING ADAPTER PS65-15-DIN ACO	CABLE DIN4-W/GT-5.5	ACCESS POINT +ROUTER ARCHER-VR300 VDSL / ADSL 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP- LINK
			
	88.02 CAD 88.02 CAD	1.48 CAD 1.48 CAD	95.46 CAD 95.46 CAD
Application	ACO Video Doorphones
Adapter type	Switching
Connector type	...	2.1/5.5 mm socket / DIN4 Straight plug	...
Frequency range	2.4 GHz, 5 GHz
Power voltage	100 ... 240 V AC
Material	...	PET	...
Output voltage	15 V DC
Length of the cable	...	10 cm	...
Antenna type	4 x Omnidirectional antenna 5 dBi
Output voltage adjustment	—
Maximal load	4 A
Output power	65 W
Number of outputs	2 pcs
Efficiency	≤ 91 %
Housing type	DIN
Standards	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5
LAN ports	• 1 x 10/100 Mbps - LAN/WAN, • 3 x 10/100 Mbps - LAN
LED indicators	Power, DSL, INTERNET, WLAN, LAN
WAN interface	• 1 x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2 • 1 x RJ-45

Transmitter power	< 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz
Baud rates	300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz
DHCP server	✓
Firmware update	✓
DDNS	• DynDNS • No-IP
Operation modes	ADSL/VDSL modem, Router, Access Point, Bridge WDS
Protections	<ul style="list-style-type: none"> • Short-circuit • Overload • Overheat 	...	<ul style="list-style-type: none"> • LAN : NAT, SPI network firewall, Access control, IP-MAC Binding, Support DoS defence, parental control • WLAN : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK, QSS (Quick Secure Setup) - WPS
Management interface	Web browser, TP-LINK Tether

Main features	...	<ul style="list-style-type: none"> • Very easy and quick assembly • Compatible with HIKVISION recorders 	<ul style="list-style-type: none"> • Enable/disable wireless network • SSID hiding • QoS • WMM (Wi-Fi Multimedia), • Rate limit • Internet access filtering • Wireless transmission statistics • Firewall • Remote management • DHCP : DHCP server, DHCP client list • Port forwarding : Virtual Server, Port Triggering, DMZ, ALG, UPnP • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, VPN Pass-through • IPv6 compliance • Static / dynamic routing • Port Mapping • IGMP Snooping V1/V2/V3 • Guest Network - a separate and secure network for guests • Built-in 4-port switch • ON/OFF button • WPS button • The WPS function allows to easy establish an encrypted connection • RESET button • The DSL line splitter included
Power supply	12 V DC / 1 A (power adapter included)
Operation temp	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 %
Weight	0.22 kg	...	0.31 kg
Dimensions	70 x 91 x 59 mm	...	257 x 160 x 37 mm
Manufacturer / Brand	ACO	...	TP-LINK
Guarantee	3 years	2 years	2 years