




	POE POWER ADAPTER RG-POE-AF15 15.6 W REYEE	DUST COVER FAN-COVER-V1	IP CAMERA DS-2CD2T47G2H-LI(4MM)(EF) ColorVu - 4 Mpx Hikvision
			
	75.00 PLN 75.00 PLN	12.60 PLN 12.60 PLN	1775.00 PLN 1775.00 PLN
Material	...	Metal	...
Standard	TCP/IP
Standards	Passive PoE
Sensor	1/1.8 " Progressive Scan CMOS
Input voltage	100 V ... 240 V AC
Matrix size	4 Mpx
Output voltage	52 V DC
Maximal output current	0.3 A
Number of inputs	1
Connector	2 x RJ-45 socket
Supported data rates	1 Gb/s
LED indicators	Power connection
Resolution	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Output power	15.6 W
Lens	4 mm
View angle	• 89 ° (manufacturer data) • 85 ° (our tests result)
White light LED illuminator range	60 m
Range of IR illumination	60 m
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)
Pin numbers for RJ-45 connector	DATA : 1, 2 and 3, 6 Power supply : 4, 5 (+) and 7, 8 (-)
Certificates	CE
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	—
Audio	—
Operation temp. / Relative humidity	-10 °C ... 45 °C / 5 % ... 95 % (non-condensing)
Main stream frame rate	25 fps @ 4 Mpx
Network interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	6
ONVIF	19.12




DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, detection of entry into the area / exit from the area - classification of people and vehicles, face detection
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	192.168.1.64
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 660 mA
Power consumption	<ul style="list-style-type: none"> • ≤ 9 W @ PoE • ≤ 8 W @ 12 V DC
Housing	Plastic	...	Compact, Metal
Color	White
"Index of Protection"	IP67
Vandal-proof	-
Operation temp	-30 °C ... 60 °C
Weight	0.09 kg	0.018 kg	1.12 kg
Dimensions	93 x 47 x 30 mm	119 x 119 x 2 mm	287 x 93 x 91 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Manufacturer / Brand	RUIJIE / REYEE	...	Hikvision
SAP Code	311323651
Guarantee	3 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00