


|   | <a href="#">ROUTER RG-EG105G-P-V2,<br/>4 PoE REYEE</a>  | <a href="#">COMBINATION WRENCH<br/>ST-STMT95912-0 19 mm<br/>STANLEY</a>           | <a href="#">IP CAMERA DS-2CD1T67G2H-LIU(2.8MM) ColorVu - 6 Mpx<br/>Hikvision</a>         | <a href="#">TEMPERATURE METER<br/>HT-6889 -50 °C... 2200 °C</a>   | <a href="#">UPS AT-UPS1200BK-LCD<br/>1200 VA EAST</a>   |
|---|---|---|--|---|---|
|   |    |  |         |    |                    |
|   | 1917.43 NOK<br>1917.43 NOK  | 51.76 NOK<br>51.76 NOK  | 2662.91 NOK<br>2662.91 NOK   | 1868.55 NOK<br>1868.55 NOK  | 1330.92 NOK<br>1330.92 NOK  |
| Standard                                | ...   | ...   | IP   | ...   | ...   |
| Size                                    | ...   | 19 mm   | ...  | ...   | ...   |
| Nominal power                           | ...   | ...   | ...  | ...   | 720 W   |
| Length                                  | ...   | 231 mm  | ...  | ...   | ...   |
| Temperature measurement range           | ...   | ...   | ...  | -50 °C ... 2200 °C  | ...   |
| Apparent Power                          | ...   | ...   | ...  | ...   | 1200 VA   |
| Input voltage                           | ...   | ...   | ...  | ...   | 173 V ... 287 V AC  |
| Standards                               | IEEE 802.3, IEEE 802.3u,<br>IEEE 802.3x, 802.3z, IEEE<br>802.3af, IEEE 802.3at  | ...   | ...  | ...   | ...   |
| Input frequency                         | ...   | ...   | ...  | ...   | 50 / 60 Hz (auto detection)   |
| Output voltage                          | ...   | ...   | ...  | ...   | 230 V AC ± 10 %<br>(Approximated Sine Wave)   |
| Resolution                              | ...   | ...   | 3200 x 1800 - 6 Mpx,<br>2688 x 1520 - 4 Mpx,<br>1920 x 1080 - 1080p<br>1280 x 720 - 720p | ...   | ...   |
| LAN ports                               | • 3 x LAN & PoE<br>10/100/1000 Mbps (RJ-45)<br>• 1 x LAN & PoE / WAN<br>10/100/1000 Mbps (RJ-45)  | ...   | ...  | ...   | ...   |
| Output frequency                        | ...   | ...   | ...  | ...   | 50 / 60 Hz ± 1 %  |
| Sensor                                  | ...   | ...   | 1/2.4 " Progressive Scan CMOS  | ...   | ...   |
| WAN interface                           | • 1 x WAN x<br>10/100/1000 Mbps (RJ-45)   | ...   | ...  | ...   | ...   |
| Lens                                    | ...   | ...   | 2.8 mm   | ...   | ...   |
| Transfer time                           | ...   | ...   | ...  | ...   | 2 ... 7 ms (typical), max.<br>10 ms   |
| View angle                              | ...   | ...   | 115 °  | ...   | ...   |
| LED indicators                          | Status, Link/Act  | ...   | ...  | ...   | ...   |
| Charging time (recover to 90% capacity) | ...   | ...   | ...  | ...   | 8 hours   |
| White light LED illuminator range       | ...   | ...   | 50 m   | ...   | ...   |
| DDNS                                    | ✓   | ...   | ...  | ...   | ...   |
| Range of IR illumination                | ...   | ...   | 50 m   | ...   | ...   |
| DHCP server                             | ✓   | ...   | ...  | ...   | ...   |
| Battery                                 | ...   | ...   | ...  | ...   | 2 pcs - 12V/7Ah   |
| Memory card slot                        | ...   | ...   | —  | ...   | ...   |
| Port USB                                | —   | ...   | ...  | ...   | ...   |
| Firmware update                         | ✓   | ...   | ...  | ...   | ...   |
| Image compression method                | ...   | ...   | H.265+ / H.265 / H.264+ / H.264 / MJPEG  | ...   | ...   |
| Accuracy of temperature measurement     | ...   | ...   | ...  | • ≤ -23 °C : ± 7 °C,<br>• -23 °C ... -2 °C : ± 4 °C<br>• -2 °C ... 94 °C : ± 2.5 °C<br>• 94 °C ... 1000 °C : ± 1 °C<br>• > 1000 °C : ± 2 °C | ...   |
| Power supply PoE                        | Power output - LAN ports :<br>PoE (802.3af/at) max. 54 W<br>(total)   | ...   | ...  | ...   | ...   |
| Estimated battery operation time        | ...   | ...   | ...  | ...   | • 57 minutes @ 100 W<br>• 14 minutes @ 300 W<br>• 8 minutes @ 500 W                                   |
| Alarm inputs / outputs                  | ...   | ...   | —  | ...   | ...   |
| Number of outputs                       | ...   | ...   | ...  | ...   | 3 pcs CEE 7/3 (Schuko)  |
| Audio                                   | ...   | ...   | • Microphone built-in,<br>• Audio transmission via network                               | ...   | ...   |
| Main stream frame rate                  | ...   | ...   | 20 fps @ 6 Mpx   | ...   | ...   |
| Measurement resolution                  | ...   | ...   | ...  | • 0.1 °C @ ≤ 1000 °C,<br>• 1 °C @ > 1000 °C   | ...   |
| Protections                             | • ACL<br>• IP-MAC Binding<br>• MAC addresses filtering<br>• Support for dynamic ARP<br>mapping and static table<br>• NAT / NAFT<br>• Port Mapping | ...   | ...  | ...   | • Fuse<br>• Overvoltage<br>• Overload protection<br>• Overcharge protection<br>• Ethernet line filter |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

|                                     |   |   |  |   |  |
|-------------------------------------|---|---|--|---|--|
| Interface                           | ...   | ...   | 10/100 Base-T (RJ-45)  | ...   | ...  |
| Response time                       | ...   | ...   | ...  | 100 ms  | ...  |
| WEB Server                          | ...   | ...   | Built-in   | ...   | ...  |
| Spectral range                      | ...   | ...   | ...  | 8 µm ... 14 µm  | ...  |
| Max. number of on-line users        | ...   | ...   | 6  | ...   | ...  |
| Management interface                | ...   | ...   | ...  | ...   | ...  |
|                                     | • Ruijie Cloud Central Management System<br>• Configuration using the Ruijie Reveye application<br>• Remote management<br>• Web browser   | ...   | ...  | ...   | ...  |
| Operation state indication          | ...   | ...   | ...  | ...   | • LCD display: operation mode, battery charging level, in/out voltage level,<br>• Sound signaling  |
| ONVIF                               | ...   | ...   | ✓  | ...   | ...  |
| Application                         | ...   | ...   | ...  | ...   | • Surveillance Systems<br>• data storage centers<br>• network, servers, workstations<br>• Industrial Equipment   |
| Housing type                        | ...   | ...   | ...  | ...   | Tower  |
| Main features                       | ...   | ...   | ...  | ...   | ...  |
|                                     | ...   | ...   | • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality<br>• WDR - 120 dB - Wide Dynamic Range<br>• 3D-DNR - Digital Noise Reduction<br>• ROI - improve the quality of selected parts of image<br>• BLC - Back Light Compensation<br>• HLC - High Light Compensation (spot)<br>• Possibility to change the resolution, quality and bit rate<br>• Horizontal mirror image<br>• Smart motion detection (with recognizing people and vehicles)<br>• Configurable Privacy Zones<br>• Sharpness - sharper image outlines<br>• video tampering<br>• Filtering of false alarms based on the recognition of persons and vehicles | ...   | ...  |
| Main features                       | ...   | ...   | ...  | ...   | ...  |
|                                     | • VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc.<br>• Static / dynamic routing<br>• WAN : PPPoE, PPTP, L2TP<br>• DHCP client/server support<br>• Access Control List - ACL package filtering based on source and destination IP addresses<br>• Rate limit<br>• Load balance<br>• NAT<br>• View topology and network status<br>• RESET button | • Product is made from chrome-vanadium steel,<br>• Full polish chrome plating for strength and durability, and easy cleaning,<br>• Corrosion resistance,<br>• Fork and polygonal head inclined by 15° for better accessibility to the nut or bolt,<br>• Anti-slip profile - wrench profile shape optimizes contact with the bolt, preventing the wrench from slipping,<br>• 12 point versatile ring spanner end for easy installation | ...  | • Built-in laser pointer,<br>• Memory of the last 100 measurements<br>• Selectable measurement unit: °C / °F<br>• Automatic sleep mode after 7 s idle time<br>• Low battery indicator<br>• Probe<br>• White backlight | • Auto restart while AC is recovering<br>• Automatic Voltage Regulator (AVR)<br>• Compatible with power generators<br>• Remote management - UPSmart application included<br>• Built-in EMI, RFI filter<br>• Configurable alarm |
| Mobile phones support               | ...   | ...   | ...  | ...   | ...  |
|                                     | Android: Free application <a href="#">Ruijie Reveye</a><br>iOS (iPhone): Free application <a href="#">Ruijie Reveye</a>   | ...   | Port no.: 8000 or access by a cloud (P2P)<br>• Android: Free application <a href="#">Hik-Connect</a><br>• iOS: Free application <a href="#">Hik-Connect</a>  | ...   | ...  |
| Operation temp. / Relative humidity | ...   | ...   | ...  | ...   | 0 °C ... 40 °C / 20 ... 90 %   |
| Default IP address                  | ...   | ...   | 192.168.1.64   | ...   | ...  |
| Operation temp                      | 0 °C ... 40 °C  | ...   | ...  | ...   | ...  |
| Default admin user / password       | ...   | ...   | admin / -<br>The administrator password should be set at the first start   | ...   | ...  |
| Web browser access ports            | ...   | ...   | 80   | ...   | ...  |
| Permissible relative humidity       | 10 % ... 90 % (non-condensing)  | ...   | ...  | < 90 %  | ...  |
| PC client access ports              | ...   | ...   | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application  | ...   | ...  |
| Mobile client access ports          | ...   | ...   | 8000   | ...   | ...  |
| Port ONVIF                          | ...   | ...   | 80   | ...   | ...  |
| RTSP URL                            | ...   | ...   | ...  | ...   | ...  |
|                                     | ...   | ...   | • Main stream :<br>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/<br>• Sub stream :<br>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/  | ...   | ...  |

|                             |   |                  |  |                                      |                    |
|-----------------------------|---|------------------|--|--------------------------------------|--------------------|
| Power supply                | 54 V DC / 1.15 A (power adapter included) | ...              | • PoE (802.3af),<br>• 12 V DC / 600 mA   | 9V, type 6F22 battery (not included) | ...                |
| Power consumption           | max. 60 W (at full load)                  | ...              | • ≤ 8.7 W @ PoE<br>• ≤ 7.2 W @ 12 V DC   | ...                                  | ...                |
| Housing                     | ...                                       | ...              | Compact, Metal   | Plastic                              | ...                |
| Color                       | ...                                       | ...              | White  | Yellow + Black                       | ...                |
| "Index of Protection"       | ...                                       | ...              | IP67   | ...                                  | ...                |
| Mechanical protection class | ...                                       | ...              | —  | ...                                  | ...                |
| Operation temp              | ...                                       | ...              | -30 °C ... 60 °C   | 0 °C ... 50 °C                       | ...                |
| Weight                      | 0.43 kg                                   | 0.162 kg         | 0.42 kg  | 0.25 kg                              | 8.57 kg            |
| Dimensions                  | 207 x 109 x 28 mm                         | 231 x 40 x 11 mm | 202 x 84 x 81 mm   | 125 x 224 x 52 mm                    | 348 x 173 x 140 mm |
| Supported languages         | ...                                       | ...              | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian | ...                                  | ...                |
| Manufacturer / Brand        | RUIJIE / REYEE                            | STANLEY          | Hikvision  | Hti                                  | EAST               |
| SAP Code                    | ...                                       | ...              | 311325502  | ...                                  | ...                |
| Guarantee                   | 2 years                                   | 2 years          | 3 years  | 2 years                              | 2 years            |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00