





	AHD, HD-CVI, HD-TVI CVBS, TCP/IP DVR XVR1B04-I 4 CHANNELS DAHUA	KRONE BACK-MOUNT FRAME LSA-GN-10/3	BOX POSITIONER PDP/EPN Elektro-Plast	WHOLE HOME WI-FI SYSTEM CUDY-M1800/2 Wi- Fi 6, 2.4 GHz, 5 GHz, 574 Mbps + 1201 Mbps
				
	510.00 PLN 510.00 PLN	7.80 PLN 7.80 PLN	38.83 PLN 38.83 PLN	420.29 PLN 420.29 PLN
Number of mounted profile modules	...	3 pcs
Number of devices included	2 pcs
Application	Marking holes for Ø68 mm multiple boxes	...
Type of mounted profile modules	...	10PAR
Frequency range	2.4 GHz, 5 GHz ,
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Antenna type	4 x Omnidirectional antenna - embedded
Material	Plastic	...
Video inputs	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Standards	IEEE 802.11ax/n/b/g @ 2.4 GHz , IEEE 802.11ax/ac/n/a @ 5 GHz
Video outputs	1 pcs HDMI 1 pcs VGA
Baud rates	574 Mbps + 1201 Mbps
Audio inputs	• 1 pcs CINCH, • 4 - Audio support via coaxial cable, HD-CVI only
Audio outputs	1 pcs CINCH
Image compression method	AI Coding / H.265+ / H.265 / H.264+ / H.264
LAN ports	1 x 10/100/1000 Mbps - WAN 1 x 10/100/1000 Mbps - LAN
LED indicators	Power / System, Link/Act
Image records resolutions	• AHD / HD-CVI / HD-TVI : 1080N - 960 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 , D1 - 720 x 576 , • IP : 1080p - 1920 x 1080

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Recording speed adjustment	1080p IP @ 1 ... 25 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Recording modes	Manual, Motion Detection, Schedule
Supported hard drives	1 x 6 TB SATA
External storage devices backup	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
DDNS	✓
DHCP server	✓
Network interface	1 x RJ-45 - 100BASE-TX
Firmware update	✓
Bitrate	32 ... 4096 kbps
Protections	WEP, WPA/WPA2, WPA- PSK/WPA2-PSK, WPA3
Management interface	Web browser
Operation modes	4 x AHD / HD-CVI / HD-TVI / CVBS / IP + 1 x IP	<ul style="list-style-type: none"> • Router, • AP, • Range Extender, • WISP
Transmitter power	<ul style="list-style-type: none"> < 20 dBm @ 2.4 GHz < 23 dBm @ 5 GHz
Network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, 3G/4G, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search

Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Alarm inputs / outputs	—
PTZ control	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI
Motion Detection	Split the screen into zones : 22 x 18 motion zones
USB	2 x USB 2.0
Main features	SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle
Mouse support	✓
IR remote controller in the set	—
Power supply	12 V DC / 1.5 A (power adapter included)	12 V DC / 1.5 A (power adapter included)
Color	Black



Main features	<ul style="list-style-type: none"> • Can be used in both horizontal and vertical orientation, • Built-in tube levels, • Mounting holes distance : 71 mm 	<ul style="list-style-type: none"> • Support for CUDY Whole Home Mesh technology • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Pairing button • RESET button • WMM (Wi-Fi Multimedia) • WAN : Fixed, or dynamic IP address, PPPoE • DHCP : DHCP server, DHCP client list, address reservation • Guest Network - a separate and secure network for guests • NAT : Port forwarding, Port Triggering, UPnP, DMZ • VPN networks: PPTP, L2TP, OpenVPN, WireGuard, IPSec, Zerotier • Access control • parental control • Remote management • VLAN • IPTV compliance • IPv6 compliance • Supports max. 100 devices • Indoor coverage area : 370 m²
Operation temp	0 °C ... 40 °C
Permissible relative humidity	max. 85 % (non-condensing)
Weight	0.54 kg	...	0.04 kg	0.42 kg
Supported languages	Polish, English, Bulgarian, Czech, Finnish, Greek, Romanian, Serbian, Slovenian, Hungarian
Country of origin	China
Dimensions	198 x 203 x 42 mm	67 x 112 x 50 mm	210 x 68 x 21 mm	Ø 110 x 155 mm
Manufacturer / Brand	DAHUA	...	Elektro-Plast Nasielsk	CUDY
Guarantee	3 years	2 years	2 years	2 years