



	SWITCH POE DS-3E1518P-SI 16-PORT SFP Hikvision	RFID PROXIMITY CARD ATLO-307*P200 13.56 MHz S50
		
	1591.00 PLN 1591.00 PLN	322.00 PLN 322.00 PLN
In package	...	200 pcs The price for package
Standard	...	13.56 MHz S50
Compatibility	...	ISO/IEC 14443A
Possibility of programming the serial number (ID)	...	—
Ability to write to internal memory	...	1 kB
Serial Number overprint	...	—
LAN ports	<ul style="list-style-type: none"> • 16 x RJ45 10/100/1000 Base-T (16 x PoE (802.3af/at)), • 2 x port SFP 1000 Base-X 	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 16 LAN & PoE ports, • 1000 Mbps - 2 SFP ports - Uplink 	...
Maximal output power	30 W / port PoE	...
Maximal total power	225 W	...
MAC addresses table	8k	...
Management	✓	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / -	...
Operation modes	<ul style="list-style-type: none"> • Extend On : 300 m, 10 Mbps @ UTP cat. 5e, 6 • Extend Off : 100 m, 1000 Mbps @ UTP cat. 5e, 6 	...

Main features	<ul style="list-style-type: none"> • Switch is web managed • Configuration and management from the iVMS-4200 application • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • View topology and network status • Data Flow Control • Storm Control function • Port mirroring function • Static link aggregation • QoS : Queue scheduling: SP, WRR, SP+WRR • VLAN • Spanning Tree STP/RSTP • SNMPv1/v2c • Watchdog PoE • The device supports 8-pin power supply • Remote configuration • Remote update of software • Can be mounted in a Rack 19" cabinet 	Range : ~ 10 cm ,
LED diodes	Power, Link/Act, PoE, PoE Max, 17 SFP, 18 SFP	...
Certificates	CE	...
Housing	Metal	...
Protections	Overvoltage 6 kV - PoE ports	...
Power supply	100 ... 240 V AC	...
Operation temp	-10 °C ... 55 °C	...
Weight	2.74 kg	0.005 kg
Dimensions	440 x 221 x 44 mm, RACK 19", 1U	86 x 54 x 0.8 mm
Manufacturer / Brand	Hikvision	ATLO
SAP Code	301802030	...
Guarantee	3 years	2 years