



	POWER SUPPLY ADAPTER ZR48-158 48 V DC 3.3 A	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500CM-IL- A-0360B-S2 - 5 Mpx 3.6 mm DAHUA
		
	281.91 PLN 281.91 PLN	376.00 PLN 376.00 PLN
Adapter type	Switching	...
Standard	...	AHD, HD-CVI, HD-TVI, CVBS
Sensor	...	Progressive Scan CMOS
Matrix size	...	5 Mpx
Power voltage	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	...
Voltage frequency range	47 ... 63 Hz	...
Output power	160 W	...
Output voltage	48 V DC	...
Output voltage adjustment	45.6 V ... 52.8 V DC	...
Maximal load	3.3 A	...
Efficiency	89 %	...
MTBF (Mean Time Between Faults)	> 700000 h - Telcordia SR-332	...
Protections	• Overvoltage • Short-circuit • Overload	...
Housing type	1 U Rack 19"	...
Operation temp. / Relative humidity	-10 °C ... 70 °C / 10 % ... 80 %	...
Resolution	...	2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps - Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Lens	...	3.6 mm
View angle	...	• 92 ° (manufacturer data) • 85 ° (our tests result)
Range of IR illumination	...	20 m
White light LED illuminator range	...	20 m
IR illuminator power adjustment	...	Automatic

Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only
OSD menu	...	✓
Main features	...	<ul style="list-style-type: none"> • Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines
Power supply	...	12 V DC / 260 mA
Power consumption	...	≤ 3.1 W
Housing	...	Compact - Metal
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-40 °C ... 60 °C
Weight	0.68 kg	0.33 kg
Dimensions	482 x 44 x 100 mm	167 x 70 x 70 mm
Manufacturer / Brand	DELTA	DAHUA
Guarantee	5 years	3 years