



	ACCESS CONTROLLER PR102DR-BRD ROGER	IP CAMERA DS-2CD1067G2H-LIU(2.8MM) ColorVu - 6 Mpx Hikvision
		
	345.01 PLN 345.01 PLN	880.00 PLN 880.00 PLN
Standard	...	IP
Environment class	I	...
Relay contacts load	1.5 A / 30 V	...
Battery backup support	—	...
Input lines	2	...
Output lines	2	...
Communication	<ul style="list-style-type: none"> • RS-485 • RACS (Roger) 	...
Resolution	...	3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Main features	<ul style="list-style-type: none"> • PRT series readers support • 4000 indexed users • History of 32000 events • Real-time clock and calendar • Remote programming from PC 	...
Sensor	...	1/2.4 " Progressive Scan CMOS
Lens	...	2.8 mm
View angle	...	115 °
Operation temp	5 °C ... 40 °C	...
White light LED illuminator range	...	30 m
Permissible relative humidity	10 ... 95 % (non-condensing)	...
Range of IR illumination	...	30 m
Memory card slot	...	—
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network
Main stream frame rate	...	20 fps @ 6 Mpx
Interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	—

Main features	...	<ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	10 ... 15 V DC	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 550 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 8 W @ PoE • ≤ 6.6 W @ 12 V DC
Housing	...	Compact, Metal
Color	...	White
"Index of Protection"	...	IP67
Mechanical protection class	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.04 kg	0.3 kg
Dimensions	80 x 54 x 18 mm	Ø 70 x 173 mm

Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand	ROGER	Hikvision
SAP Code	...	311325494
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00