




	NVR NVR302-32E2-IQ 32 CHANNELS UNIVIEW	FLUSH BOX 3-GANG PK-3X60/K-G/SG/EPN Elektro-Plast
		
	2695.84 PLN 2695.84 PLN	16.95 PLN 16.95 PLN
Standard	TCP/IP	...
Number of sections	...	3
Supported resolutions	max. 12 Mpx - 4000 x 3000 px	...
"Index of Protection"	...	—
Video outputs	1 pcs HDMI 4K 1 pcs VGA	...
Audio support	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support 	...
Main features	...	<ul style="list-style-type: none"> • Flush-mounted, for hollow walls • 4 special screws with holders to fastening to the wall - included
Audio inputs	1 pcs CINCH	...
Material	...	Plastic
Color	...	Yellow
Audio outputs	1 pcs CINCH	...
Image compression method	Ultra 265 / H.265 / H.264	...
Montage hole diameter	...	3 x Ø 67 mm
Bitrate	max. 320 Mbps	...
Supported hard drives	2 x 8 TB SATA	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/6/8/9/16/25/36 channel synchronous playback	...
Network interface	2 x RJ-45 10/100/1000 Base-TX	...
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users	...

Network protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS	...
ONVIF	✓	...
Default IP address	DHCP or 192.168.1.30	...
Default admin user / password	admin / 123456	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
RTSP URL	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream	...
USB	2 x USB 2.0 1 x USB 3.0	...
Serial ports	RS-485	...
Alarm inputs / outputs	8 / 2	...
PTZ control	• PTZ Uniview cameras • RS-485 control	...
Motion Detection	✓	...
Intelligent image analysis	✓	...
Main features	• Motion detection with human/vehicle silhouette recognition • Filtering of false alarms based on the recognition of persons and vehicles	...
Mouse support	✓	...
IR remote controller in the set	—	...
Switch PoE	—	...
Power supply	12 V DC / 3.3 A (power adapter included)	...
Power consumption	max. 12 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...
Weight	1.77 kg	0.068 kg
Dimensions	380 x 322 x 53 mm	3 x Ø 60 x 47 mm - Internal dimensions 211 x 72 x 48 mm - External dimensions

Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian	...
Manufacturer / Brand	UNIVIEW	Elektro-Plast
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00