



	<a href="#">VIDEO BALUN TR-1/PVD*P2</a>	<a href="#">TOOL FOR CLEANING FIBER OPTIC CONNECTORS WUN-015 MU / LC</a>
		
	19.20 PLN 19.20 PLN	88.55 PLN 88.55 PLN
In package	<b>2 pcs The price for package</b>	...
Application	...	Ideal for removing dirt from optical components Connector type : MU / LC
Standard	<ul style="list-style-type: none"> <li>• AHD - 8 Mpx 4K UHD,</li> <li>• HD-CVI - 8 Mpx 4K UHD,</li> <li>• HD-TVI - 8 Mpx 4K UHD,</li> <li>• CVBS - PAL, NTSC</li> </ul>	...
Device type	Passive	...
Number of channels	1 x Video 1 x DC 1 x DATA	...
Coaxial socket voltage range 75Ω (CVBS)	1 Vpp	...
Video transmission range	<ul style="list-style-type: none"> <li>• 250 m @ 720p - UTP cat. 5e</li> <li>• 150 m @ 1080p - UTP cat. 5e</li> <li>• 400 m @ CVBS - PAL / NTSC - UTP cat. 5e</li> </ul>	...
Attenuation	<ul style="list-style-type: none"> <li>• 4.43 MHz @ 0.46 dB</li> <li>• 11 MHz @ 0.68 dB</li> <li>• 21 MHz @ 0.98 dB</li> <li>• 38 MHz @ 1.72 dB</li> <li>• 42 MHz @ 1.82 dB</li> <li>• 67.5 MHz @ 2.00 dB</li> </ul>	...
Symmetrical socket impedance	100 Ω	...
Connectors type	<ul style="list-style-type: none"> <li>• Video - BNC, Plug with cable</li> <li>• Plug / Socket DC - 2.1 / 5.5 mm</li> <li>• DATA - pair of wires : Black + Red</li> </ul>	...
Symmetrical socket type	RJ-45 (8-pin, 4 pairs) Socket	...
Permissible relative humidity	< 95 %	...

Operation temp	-20 °C ... 70 °C	...
Power supply distance	<ul style="list-style-type: none"> <li>• Power supply 12V DC</li> <li>118 m @ 100 mA</li> <li>79 m @ 150 mA</li> <li>59 m @ 200 mA</li> <li>47 m @ 250 mA</li> </ul>	...
Weight	0.04 kg	0.02 kg
Dimensions	63 x 33 x 25 mm	183 x 18 x 18 mm
Guarantee	2 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00