





	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA48VWR6-G(2) - 8 Mpx, 4K UHD 2.7 ... 13.5 mm - MOTOZOOM	HDD ENCLOSURE Y-3036 UNITEK	HUB USB 3.0 HUB-USB3.0-1/7 55 cm	SWITCH DISCONNECTOR WITH FUSE LE-606706 THREE-PHASE 25 A D02 LEGRAND
				
	535.00 PLN 535.00 PLN	51.50 PLN 51.50 PLN	41.14 PLN 41.14 PLN	334.69 PLN 334.69 PLN
Device type	Three-phase
Rated current	25 A
Supported hard drives	...	1 x SATA III, 2.5 "
Number of poles	3
Standard	AHD / HD-CVI / HD-TVI / CVBS
Rated voltage	400 V AC
Rated insulation voltage	500 V
Outputs	...	1 x USB 3.1, max. 5 Gb/s
Connectors	<ul style="list-style-type: none"> • 1 x socket - USB 3.0 Micro B • 7 x socket - USB 3.0 A • 1 x Power socket - 1.35 / 3.50 mm 	...
Rated impulse withstand voltage	6000 V
Operation state indication	...	LED diodes
Length of the cable	55 cm	...
Fusing characteristics	gL/gG
USB standard	3.0	...
Type (size)	D02
Breaking capacity	50000 A AC
Connectors type	cable terminals
Wire gauge	2.5 ... 25 mm ²
Environment class	II
Main features	<ul style="list-style-type: none"> • Solid workmanship • It can be used as a charger for multiple devices when connected to an external power source via the 3.50 / 1.35 mm socket • LED indication • The cable included in the kit: USB 3.0 A plug / USB 3.0 Micro B plug • Each socket has a separate switch 	...
Width in 17.5 mm modules	4.5
Operation temp	-26 °C ... 60 °C

Resolution	3840 x 2160 - 8 Mpx, 4K UHD @ AHD / HD-TVI / HD-CVI, 15 fps , 2880 x 1620 - 5 Mpx @ AHD / HD-TVI / HD-CVI, 25 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI, 30 fps / 25 fps , 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI, 30 fps / 25 fps , 960 x 576 - 960H @ CVBS
Sensor	1/2.7 " CMOS
Lens	2.7 ... 13.5 mm - Motozoom
View angle	114 ° ... 32 °
Range of IR illumination	60 m
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	✓
OSD menu	✓
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • Auto White Balance • F-DNR (Defog) - Reduction of image noise caused by precipitation • 3D-DNR - Digital Noise Reduction • AGC - Automatic Gain Control • Day/night mode • ICR - Movable InfraRed filter
Power supply	12 V DC / 670 mA	Port USB
Power consumption	< 8 W
Housing	Dome, Metal	Desktop, Plastic	...	Plastic, TH-35 rail mounting
Color	Graphite
"Index of Protection"	IP67
Mechanical protection class	—
Operation temp	-30 °C ... 60 °C
Weight	0.600 kg	0.08 kg	0.050 kg	0.524 kg
Dimensions	Ø 122 x 105 mm	131 x 83 x 35 mm	165 x 36 x 25 mm	83 x 70.3 x 79.5 mm
Supported languages	Polish, English
Manufacturer / Brand	BCS UNIVERSAL	UNITEK	...	LEGRAND
Guarantee	3 years	2 years	2 years	2 years