



	ACCESS CONTROLLER ASC2202B-S DAHUA	NVR DS-7104NI-Q1/M(D) 4 CHANNELS Hikvision
		
	887.00 PLN 887.00 PLN	511.00 PLN 511.00 PLN
Number of served transitions	2 (one-way)	...
Standard	...	TCP/IP
Supported resolutions	...	max. 6 Mpx
Support	DAHUA	...
Number of supported readers	4 pcs	...
Video outputs	...	1 pcs HDMI 1 pcs VGA
Battery backup support	—	...
Audio support	...	4 Channels - Audio from cameras
Output lines	2 pcs - Relay	...
Audio inputs	...	—
Audio outputs	...	—
Communication	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand 	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Bitrate	...	max. 40 Mbps
Supported hard drives	...	1 x 6 TB SATA
Recording modes	...	Manual, Motion Detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Records playback from max. 4 channels in the same time @ 1080p 1 or 4 channels synchronous playback, Smart Search function
Network interface	...	1 x RJ-45 10/100 Base-TX

Main features	<ul style="list-style-type: none"> • 100000 indexed users • History of 500000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Possibility to mount on a wall, or on the DIN TS-35 rail 	...
Network functions	...	Live image view, Playback the records, Backup the records - iVMS-4200 application The device has the ability to work with the Hik-Connect application for mobile devices
Permissible relative humidity	5 % ... 90 % (non-condensing)	...
Network protocols	...	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP
ONVIF	...	✓
Default IP address	192.168.0.2	192.168.1.64
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ <ul style="list-style-type: none"> • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/
USB	...	2 pcs USB 2.0
Alarm inputs / outputs	...	—
Intelligent image analysis	...	✓

Main features	...	Functions implemented in cooperation between the recorder and cameras that support these functions <ul style="list-style-type: none"> • IVS analysis : crossing the line (tripwire), intrusion • Motion Detection
PTZ control	...	IP Speed Dome Cameras
Motion Detection	...	✓
Mouse support	...	✓
IR remote controller in the set	...	—
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 4 A 	12 V DC / 1.5 A (power adapter included)
Power consumption	...	≤ 10 W (without HDD)
Operation temp	-30 °C ... 60 °C	-10 °C ... 55 °C
Weight	0.27 kg	0.8 kg
Dimensions	155 x 116 x 50 mm	265 x 223 x 48 mm
Supported languages	...	Polish, English
Manufacturer / Brand	DAHUA	Hikvision
SAP Code	...	303618105
Guarantee	3 years	3 years

