




	TV OR MONITOR MOUNT BRATECK-PLB-CE344	COAXIAL CABLE RF-7 50 Ω	TV OR MONITOR MOUNT BRATECK-LP42-69T
			
	98.49 PLN 98.49 PLN	8.11 PLN 8.11 PLN	84.62 PLN 84.62 PLN
In section	...	100 m . Price for 1m when buying a whole roll	...
Inner conductor	...	Ø 1.85 mm Cu ± 0.05 mm - Cu stranded wire	...
Dielectric	...	Ø 5 mm - Physical foam	...
Shield	...	Double-sided foil - Cu/PET/Cu	...
Braid	...	80 % Cu	...
Impedance	...	50 Ω	...
Mounting standard	VESA 75, 100, 200, 200x100, 400, 400x200	...	VESA 75, 100, 150, 200, 200x100, 300, 400x200, 400x300, 400, 600x400, 600, 800x600, 900x600
Screen size range	32 " ... 55 "	...	60 " ... 100 "
Outer coating	...	Ø 7.3 mm ± 0.2 mm PE - Black	...
Bearing capacity	50 kg	...	75 kg
Distance from mounting surface	(manufacturer data) : 1050 ... 1560 mm from ceiling Our tests results : 920 ... 1510 mm from ceiling	...	85 mm
Color	Black	...	Black
Horizontal rotation	360 °
Rotation in the plane of the screen	—
Tilt adjustment	-15 ° ... 15 °	...	-10 ° ... 5 °
Main features	...	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • it can be used in WLAN 2,4GHz and 5GHz installations • Operation temp : -30 °C ... 70 °C 	...
Weight	5.7 kg	...	3.7 kg
Dimensions	1080 x 520 x 60 mm	...	954 x 625 x 85 mm

Cable attenuation at 100m section	...	2 dB @ 10 MHz 6.4 dB @ 100 MHz 9.1 dB @ 200 MHz 14.1 dB @ 500 MHz 20.9 dB @ 800 MHz 25.9 dB @ 1 GHz 31 dB @ 1.5 GHz 35 dB @ 2 GHz 39 dB @ 2.5 GHz	...
Maximum transmitted power	...	3.27 kW @ 10 MHz 1.025 kW @ 100 MHz 0.693 kW @ 200 MHz 0.452 kW @ 500 MHz 0.310 kW @ 800 MHz 0.253 kW @ 1 GHz 0.219 kW @ 1.5 GHz 0.195 kW @ 2 GHz 0.175 kW @ 2.5 GHz	...
Guarantee	2 years	2 years	2 years