






	ALKALINE BATTERY BAT-AAA/E-MAX*P16 1.5 V LR3 (AAA) ENERGIZER	FIBER OPTIC VIDEO CONVERTER OVH-1D/SC 1X VIDEO + RS-485 TXRX SET	FLUSH-MOUNTING DISTRIBUTION CABINET 12-MODULAR ELEGANT-1X12/PT/W/EPN Elektro-Plast	IP CAMERA APTI-AI203PV21-28W - 1080p 2.8 mm	DVI + USB SWITCH CS-22D
					
	31.45 PLN 31.45 PLN	318.40 PLN 318.40 PLN	48.24 PLN 48.24 PLN	126.08 PLN 126.08 PLN	281.52 PLN 281.52 PLN
Method of mounting	Flush-mounted
Standard	TCP/IP	...
Input	2 pcs DVI + 2 pcs USB
Sensor	1/2.9 " Progressive Scan CMOS	...
Output	1 pcs DVI + 2 pcs USB
In package	16 pcs The price for package
Number of mounted modules	12 x 1 row, 17.5 mm
Standard	...	AHD / HD-CVI / HD-TVI / PAL
Matrix size	2.1 Mpx	...
Rated voltage	1.5 V
Spacing between TH 35 rails	—
Optical connector type	...	SC
Type (size)	LR3 (AAA)
Transparent door	✓
Number of fibers	...	1 pcs
Recommended fiber	...	Single-mode fiber
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Transmission range	...	20 km - Single-mode fiber
Lens	2.8 mm	...
View angle	105 °	...
Range of IR illumination	30 m	...
Main features	<ul style="list-style-type: none"> • Alkaline batteries last 50% longer than basic alkaline batteries, • Powerful and high performance, • Holds power for up to 10 years of shelf life, • Leak-proof construction 	...	Removable chassis with TH 35 rails
Equipment	Terminal blocks : • 1 pcs N : 6 x 10 mm ² + 8 x 16 mm ² • 1 pcs PE : 6 x 10 mm ² + 8 x 16 mm ²
Material	Plastic
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Number of video channels	...	1 pcs - AHD / HD-CVI / HD-TVI / PAL
Alarm inputs / outputs	—	...
Audio	—	...
IK rating	—	...
Main stream frame rate	25 fps @ 1080p	...
Compliance with standards	IEC/EN 62208, IEC/EN 60670-24
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in - port 80	...
Max. number of on-line users	10	...
ONVIF	✓	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported resolutions	...	<ul style="list-style-type: none"> • AHD : 8 Mpx 4K UHD @ 15 fps, 5 Mpx, 4 Mpx, 3 Mpx, 1080p, 720p @ 25 / 20 / 12.5 fps, • HD-CVI : 1080p, 720p @ 25 fps, • HD-TVI : 5 Mpx @ 12.5 fps, • CVBS : 1080p @ 25 fps 	max. 1920 x 1200 px
Video connectors type	...	BNC
Video resolution	...	8 bit
Video bandwidth	...	0 MHz ... 50 MHz
Video input voltage / impedance	...	1 Vpp / 75 Ω
Main features	<ul style="list-style-type: none"> • Intelligent image analysis : intrusion, motion detection based on human detection • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • Possibility to change the resolution, quality and bit rate • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Motion Detection • Privacy zones • Day/night mode • Auto White Balance • Mirror - Mirror image • RESET button - on the cable • Sharpness - sharper image outlines 	...
Audio input	...	—
Mobile phones support	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision 	...
Default IP address	192.168.1.168	...
RS-485 signal	...	one-direction RS-485 Connectors 1 (+), 2 (-) - terminals
Default admin user / password	admin / - The administrator password should be set at the first start	...
Optical wavelength	...	1310 / 1550 nm
Web browser access ports	80	...
PC client access ports	80	...
LED diodes	...	LEDs indicating device operation state
Mobile client access ports	80	...
Port ONVIF	80	...
Operation temp	...	-40 °C ... 75 °C
RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...
Permissible relative humidity	...	0 % ... 95 % (non-condensing)
Power supply	...	5 V DC / 1.0 A (power adapter included)	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 220 mA 	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power consumption	≤ 2.7 W	...
Housing	Dome, Metal + Plastic	...
Vandal-proof	—	...
Color	White	White	...
"Index of Protection"	IP40	IP65	...
Operation temp	-20 °C ... 60 °C	...
Weight	0.012 kg	0.234 kg	0.82 kg	0.23 kg	0.34 kg
Dimensions	...	108 x 121 x 28 mm	303 x 214 x 112 mm	Ø 108 x 83 mm	100 x 107 x 30 mm
Supported languages	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, Portuguese, Russian, Turkish	...
Manufacturer / Brand	ENERGIZER	...	Elektro-Plast Nasielsk	APT1	ATEN
Guarantee	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00