

	<a href="#">IP CAMERA DS-2CD2087G2H-LIU(4MM)(EF) ColorVu - 8.3 Mpx 4K UHD Hikvision</a>	<a href="#">HUB USB 3.0 BT2U3-7AB-EU-GY-BP 1 m</a>
		
	2435.00 PLN 2435.00 PLN	117.15 PLN 117.15 PLN
Standard	TCP/IP	...
Sensor	1/1.8 " Progressive Scan CMOS	...
Matrix size	8.3 Mpx	...
Connectors	...	<ul style="list-style-type: none"> <li>• 1 x Socket - USB-B 3.0</li> <li>• 7 x socket - USB-A</li> <li>• 1 x Power socket - 5.5/2.1 socket</li> </ul>
Length of the cable	...	1 m
USB standard	...	3.0
Main features	...	<ul style="list-style-type: none"> <li>• Solid workmanship</li> <li>• LED indication</li> <li>• Each socket has a separate switch</li> </ul>
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Lens	4 mm	...
View angle	<ul style="list-style-type: none"> <li>• 90 ° (manufacturer data)</li> <li>• 85 ° (our tests result)</li> </ul>	...
White light LED illuminator range	40 m	...
Range of IR illumination	40 m	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> <li>• Noise and echo reduction</li> </ul>	...
Main stream frame rate	25 fps @ 8.3 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	19.12	...

Main features	<ul style="list-style-type: none"> <li>• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, detection of entry into the area / exit from the area, face detection</li> </ul>	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 580 mA</li> </ul>	12 V DC / 2 A (included)
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 8.5 W @ PoE</li> <li>• ≤ 7 W @ 12 V DC</li> </ul>	...
Housing	Compact, Metal	Aluminum
Color	White	...
"Index of Protection"	IP67	...

Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.52 kg	0.186 kg
Dimensions	234 x 120 x 117 mm	145 x 58 x 28 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	...
Manufacturer / Brand	Hikvision	ORICO
SAP Code	311323640	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00