




	<a href="#">WHOLE HOME WI-FI SYSTEM DECO-M5(1-PACK) 2.4 GHz, 5 GHz 400 Mbps + 867 Mbps TP-LINK</a>	<a href="#">CABLE MANAGER TRSH-8*P10</a>	<a href="#">HOOK &amp; LOOP TAPE ON-OFF-TAPE/1MX20/BLACK TESA</a>	<a href="#">EXTENDER ETHERNET+PoE ETH-ETH500-SET ATTE</a>
				
	109.48 EUR 109.48 EUR	1.36 EUR 1.36 EUR	3.60 EUR 3.60 EUR	60.43 EUR 60.43 EUR
Number of devices included	1 pcs	...	...	...
Length	...	...	1 m	...
Frequency range	2.4 GHz, 5 GHz	...	...	...
Width	...	...	20 mm	...
In package	...	<b>10 pcs The price for package</b>	...	...
Hole diameter	...	Ø 8 mm	...	...
Antenna type	4 x Omnidirectional antenna - embedded	...	...	...
Mounting methods	...	...	self-adhesive tape	...
LED diodes	...	...	...	LAN, PoE, 10Mb
Assembly	...	The bottom layer is equipped with a Scotch tape	...	...
UTP transmission range	...	...	...	< 800 m (max)
Color	...	Black	Black	...
Material	...	Plastic	...	...
Transmission speed	...	...	...	10 / 100 Mbps : 2 LAN & PoE ports
Standards	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz	...	...	...
Baud rates	400 Mbps + 867 Mbps	...	...	...
LAN ports	2 x 10/100/1000 Mbps	...	...	2 x RJ45 10/100 Base-T + Passive PoE
LED indicators	✓	...	...	...
DDNS	✓	...	...	...
DHCP server	✓	...	...	...
Firmware update	Automatic	...	...	...
Maximal output power	...	...	...	< 250 m - 100 Mbps - 50 W < 500 m - 100 Mbps - 25 W < 800 m - 10 Mbps - 15 W
Maximal total power	...	...	...	50 W
Protections	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding	...	...	...

Management interface	Web browser, TP-LINK Tether	...	...	...
Transmitter power	max. 20 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz	...	...	...
Power supply	12 V DC / 1.2 A (power adapter included)	...	...	44 ... 58 V DC - Passive PoE 12 ... 58 V DC - screw connectors
Power consumption	...	...	...	1.35 W
Main features	<ul style="list-style-type: none"> <li>• The Deco Mx offers a stable connection with speeds up to 1.5 Gb/s and is compatible with all cable modems, and the entire system can support up to 100 wireless devices in the network</li> <li>• TP-Link Mesh technology: MU-MIMO, Automatic route selection, AP control, Bandwidth control, Beamforming</li> <li>• Port forwarding</li> <li>• IPv4/IPv6</li> <li>• Guest Network - a separate and secure network for guests</li> <li>• Black list</li> <li>• Firewall</li> <li>• WMM (Wi-Fi Multimedia)</li> <li>• Internet access filtering</li> <li>• Access control, parental control</li> <li>• Remote management</li> <li>• Static / dynamic routing</li> <li>• Wireless transmission statistics</li> </ul>	...	...	<ul style="list-style-type: none"> <li>• Can be powered from a switch (PoE 802.3at/af, Passive PoE) and via screw connectors</li> <li>• Possibility to connecting in cascade</li> <li>• The device can function as a LAN network and PoE power extender</li> <li>• The output PoE voltage is equal to the input voltage</li> </ul>
System requirements	<ul style="list-style-type: none"> <li>• Android 4.3 or newer</li> <li>• iOS 8.0 or newer</li> <li>• Bluetooth 4.0 or newer</li> </ul>	...	...	...
Operation temp	0 °C ... 40 °C	...	...	...
Permissible relative humidity	10 % ... 90 % (non-condensing)	...	...	...
Weight	0.22 kg	...	0.029 kg	0.05 kg
Dimensions	Ø 120 x 37 mm	...	...	73 x 52 x 20 mm (single element)
Manufacturer / Brand	TP-LINK	...	TESA	ATTE
Guarantee	3 years	2 years	2 years	3 years