



	SMART LED LIGHTING CONTROLLER WLIGHTBOX-V3/BLEBOX Wi-Fi, 12 ... 24 V DC	KEYSTONE CONNECTOR FX-RJ45-8.1 DIGITUS
		
	48.51 CAD 48.51 CAD	18.36 CAD 18.36 CAD
Connector type	...	RJ-45 shielded socket
Application	Works with LED lighting - (RGB/RGBW/RGBCCCT/CCT/MONO) 12-24V LED strips	...
Wire mounting	...	KRONE quick-connector - locked
Rated voltage	12 ... 24 V DC	...
Maximal total load	360 W	...
Application	...	<ul style="list-style-type: none"> • Patch panel Keystone, • STP cat. 8.1
Impedance	...	100 Ω
Material	...	Metal + Plastic
Total maximal current	15 A (3 A / Channel)	...
Number of inputs	1	...
Number of outputs	5	...
Connector type	screw terminals	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	...
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS 	...

Main features	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • Controlling the color, color temperature, brightness, effect, changing time allows any interior arrangement • predefined effects, • effects modification, • Operation modes : <ul style="list-style-type: none"> - 1 x RGB (color) - 1 x RGBW (color + white - brightness control) - 1 x RGBWW / RGB CCT (color + white - brightness and color temperature control) - 1 x RGB (color) + 1 x MONO (single color) - 1 x CCT (white - brightness and color temperature control) - 2 x CCT (white - brightness and color temperature control) - 1 x RGB (color) + 1 x CCT (white - brightness and color temperature control) - 5 x MONO (single color) / halogen bulb • µWiFi technology support 	<ul style="list-style-type: none"> • Very easy and quick installation without any tools • Corrosion resistance • Keystone assembly standard • The die-cast metal body provides effective shielding and high mechanical resistance • Bandwidth : ≤ 2000 MHz, • Supported data rates : 25/40GBase-T, • Supported norms : ISO/IEC 11801-3, PN-EN-50173-1, EIA/TIA 568-C, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt • PoE, PoE+, 4PPoE compliance • Gold-plated connector prevents the oxidation of contacts • Operation temp : -20 °C ... 70 °C
Housing	Plastic	...
"Index of Protection"	IP20	...
Color	Black	Silver
Operation temp	-20 °C ... 50 °C	...
Weight	0.026 kg	0.025 kg
Dimensions	43 x 35 x 18 mm	16.4 x 22 x 34 mm (W x H x D)
Manufacturer / Brand	BleBox	DIGITUS
Guarantee	2 years	2 years