



	ENCLOSURE TSM-K4 395 x 306 x 160 mm	SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH-2WIRE-A-SET 2 PCS SET ATTE
		
	54.40 PLN 54.40 PLN	469.00 PLN 469.00 PLN
Material	Steel - powder painted	...
Color	Light gray	...
Mounting plate	Steel	...
Plate thickness	1 mm	...
Connectors	...	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm² (22 ... 12 AWG)
LAN ports	...	1 pcs RJ45 10 / 100 Mbps
Housing external dimensions	395 x 306 x 160 mm / 180 mm (with cover)	...
Internal dimensions	<ul style="list-style-type: none"> • 335 x 255 x 130 mm • 335 x 235 mm (mounting desk) 	...
Terminals	...	<p>ETH-2WIRE-A-TX :</p> <ul style="list-style-type: none"> • PoE IN - Passive PoE ≤ 30 W, PoE (802.3af) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+"-": 3, 6 pins) or ("+"-": 4, 5 pins; "+"-": 7, 8 pins) • Power • DATA - 2-wire <p>ETH-2WIRE-A-RX :</p> <ul style="list-style-type: none"> • PoE OUT - Hi-PoE (802.3af/at/bt) ("+"-": 3, 6 / 4, 5 pins; "-"-": 1, 2 / 7, 8 pins) • Power • DATA - 2-wire
Transmission speed	...	10 / 100 Mbps
Transmission range	...	<ul style="list-style-type: none"> • 300 m @ 100 Mbps : 2-wire, • 800 m @ 10 Mbps : 2-wire • 100 m @ UTP : Switch PoE - ETH-2WIRE-A-TX • 100 m @ UTP : ETH-2WIRE-A-RX - IP Camera

LED indicators	...	<ul style="list-style-type: none"> • Power • LAN (RJ-45) • PoE (RJ-45) • 2-wire • 2-wire 10 Mbps • LV - low voltage < 44 V
Protections	...	<ul style="list-style-type: none"> • Overvoltage - LAN, DATA • Protection against reverse polarity connection - Power • Overload 0.6 A - PoE IN ETH-2WIRE-A-TX
Main features	<ul style="list-style-type: none"> • Holes for cables from the bottom : 2 x 3 pcs • 2 keys (included) 	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks
Power supply	...	ETH-2WIRE-A-TX : <ul style="list-style-type: none"> • 24 ... 56 V DC - PoE • 12 ... 56 V DC - Power ETH-2WIRE-A-RX : <ul style="list-style-type: none"> • 44 ... 56 V - Power • The output PoE voltage is equal to the input voltage
Power consumption	...	1.35 W (total)
Housing	...	Plastic (polycarbonate)
"Index of Protection"	...	IP20
Operation temp	...	-25 °C ... 65 °C
Weight	3.17 kg	0.028 kg (single element)
Dimensions	...	73 x 51 x 23 mm (single element)
Manufacturer / Brand	...	ATTE
Guarantee	2 years	3 years