



	<a href="#">WI-FI SMART PLUG ABAX/ABAX2 ASW-200-F 2300 W SATEL</a>	<a href="#">POWER DISTRIBUTION UNIT ACAR-S8-DUAL</a>
		
	24038.46 HUF 24038.46 HUF	9573.08 HUF 9573.08 HUF
Rated voltage	230 V AC, 50 / 60 Hz	230 V AC / 50 Hz
Nominal load current	...	10 A (total)
Maximal total load	2300 W	...
Total maximal current	10 A	...
Nominal voltage of surge suppressor	...	250 V / 50 Hz
Power consumption	1 W (Standby mode)	...
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)
Number of outlets	1 pcs	8 grounded outlets 10A/250V
Automatic delayed fuse	...	✓
Socket type	CEE 7/3 (Schuko)	...
Plug type	CEE 7/7	...
Nominal stroke current	...	2 kA (L/N) - 8/20 μs
Grounding	✓	...
Maximum stroke current	...	6.5 kA (L/N) - 8/20 μs
Wireless	Satel ABAX/ABAX2, 868.0 ... 868.6 MHz	...
Response time	...	< 25 ns
Switch	...	two-way, with light indication
Length of the cable	...	1.4 m

Main features	<ul style="list-style-type: none"> <li>• Remote update of software,</li> <li>• Remote configuration,</li> <li>• Bi-directional encrypted radio communication - AES,</li> <li>• Frequency hopping against jamming for reliable transmission,</li> <li>• LED indication - Current consumption / Failure signaling</li> <li>• Operation modes : manual / manual or remote access / manual or remote access ( blocking function )</li> <li>• ON/OFF button</li> <li>• Operating range in open area : 1000 m ABAX2, 500 m ABAX</li> <li>• Protections : Overload, Overheat</li> <li>• Easy operation</li> <li>• Environmental class EN 50130-5 : II</li> <li>• Supported norms : EN50130-4, EN50130-5</li> </ul>	...
Housing	Plastic	Plastic - non-flammable
Color	Light gray	...
Operation temp	-10 °C ... 55 °C	...
Permissible relative humidity	max. 93 % ± 3 %	...
Weight	0.062 kg	0.52 kg
Dimensions	Ø 45 x 70 mm	445 x 54 x 55 mm
Manufacturer / Brand	SATEL	...
Guarantee	2 years	2 years