



	IP CAMERA BCS-L-TIP4-2MWSCL4RBS-F-M-A-AI1 NightColor - 1080p 2.8 mm	INTERFACE FOR SYSTEM INTEGRATION INT-RS-PLUS SATEL
		
	629.40 PLN 629.40 PLN	402.00 PLN 402.00 PLN
Standard	TCP/IP	...
Support	...	INTEGRA, INTEGRA Plus
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	2.1 Mpx	...
Application	...	<ul style="list-style-type: none"> • Connecting a computer with the GUARDX applicztion installed (same as for the LCD keypad) • Event monitoring via specialized third-party external modules • Operation of the control panel with the help of software other than that offered by SATEL (possibility of integration with other systems)
Main features	...	Galvanic separation protecting against potential difference
Current consumption	...	max. 40 mA
Environment class	...	II
Operation temp	...	-10 °C ... 55 °C
Resolution	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Scanning system	Progressive	...
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> • 107 ° (manufacturer data) • 103 ° (our tests result) 	...
White light LED illuminator range	≤ 40 m	...
Min. illumination	0.0015 Lux / F1.0 (color)	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / 1	...

Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • External microphone input, • Audio output, • Bi-directional audio streaming support, • Audio detection 	...
Main stream frame rate	25 fps @ 1080p	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	20.06	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager 	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Day/Night mode (color/b&w/auto) • Full Color - colorful night mode • Auto White Balance • AGC - Automatic Gain Control • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • Light and sound alarm • Active deterrence function • White light (LED) illuminator built-in : 2 LEDs • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, scene changing, Audio detection 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 600 mA 	12 V DC



Power consumption	max. 8.5 W @ PoE max. 7.2 W @ 12 V	...
Housing	Compact - Metal	...
Color	White + Black	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-40 °C ... 60 °C	...
Weight	1.01 kg	0.04 kg
Dimensions	289 x 95 x 85 mm	63 x 80 x 18 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	BCS	SATEL
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00