




	IP SPEED DOME CAMERA OUTDOOR OMEGA- AI50P18-15 - 5 Mpx 5.35 ... 96.3 mm	CLEANING PASTE PEVALIN- PROFESSIONAL/500 500 ml TESA
		
	1182.40 PLN 1182.40 PLN	51.13 PLN 51.13 PLN
Standard	TCP/IP	...
Package	...	500 ml
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	5 Mpx	...
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Lens	5.35 ... 96.3 mm	...
View angle	• 59 ° ... 3.6 ° (manufacturer data) • 46 ° ... 3.5 ° (our tests result)	...
Optical zoom	x 18	...
Auto IR illuminator	Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions	...
Range of IR illumination	120 m	...
S/N ratio	≥ 50 dB (AGC off)	...
Video output	—	...
Rotation speed (manual control)	1 °/s ... 120 °/s (horizontal) 1 °/s ... 60 °/s (vertical)	...
Horizontal rotation range	360 ° continuous	...
Vertical rotation range	0 ° ... 93 °	...
RS-485 interface	—	...
Number of presets	255	...
Horizontal scan	✓	...
Image compression method	H.265 / H.264	...
Protections	Overvoltage	...
Alarm inputs / outputs	—	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP	...

Main stream frame rate	<ul style="list-style-type: none"> • 20 fps @ 5 Mpx • 25 fps @ 4 Mpx 	...
WEB Server	Built-in	...
ONVIF	✓	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision 	...
Default IP address	192.168.1.168	...
Default admin user / password	admin / admin	...
Web browser access ports	80	...
Port ONVIF	8999	...
RTSP URL	rtsp://ip_address/1/h264major - Main stream rtsp://ip_address/1/h264minor - Sub stream	...
Route settings	3	...
OSD menu	preset 95	...
Main features	<ul style="list-style-type: none"> • Intelligent image analysis : intrusion, motion detection based on human detection, video tampering • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • LDC - lens distortion correction • ICR - Movable InfraRed filter • BLC - configurable Back Light Compensation • Auto White Balance • IR illuminator optimization • Mirror - Mirror image • Privacy zones - max. 3 	...
Power supply	12 V DC / 3 A (power adapter included)	...
Power consumption	≤ 33 W	...
Housing	Speed Dome, Metal	...
Color	White + Black	...
"Index of Protection"	IP66	...
Operation temp	-20 °C ... 60 °C	...
Weight	2.34 kg (with bracket)	...

Dimensions	340 x 275 x 188 mm (with bracket)	...
Supported languages	English	...
Manufacturer / Brand	OMEGA	TESA
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00