

	TV OR MONITOR MOUNT BRATECK-LPA78-446	HEX REGULAR NUT N- M6/KL-8	ROUTER ER-X EdgeMAX UBIQUITI	IP CAMERA IPC3612LB-SF40-A - 1080p 4 mm UNIVIEW
				
	4815.24 HUF 4815.24 HUF	5.71 HUF 5.71 HUF	26005.71 HUF 26005.71 HUF	41260.00 HUF 41260.00 HUF
Size	...	M6
Standard	TCP/IP
Standards	IEEE 802.3ad, IEEE 802.1q	...
Material	...	Steel galvanized
Sensor	1/2.8 " Progressive Scan CMOS
Processor	Dual-Core 880 MHz, MIPS1004Kc	...
Strength class	...	8
Matrix size	2.1 Mpx
Scanning system	Progressive
LAN ports	5 x LAN 10/100/1000 Mbps (RJ-45)	...
WAN interface	configurable	...
Wrench size	...	10 mm
Thickness	...	5 mm
LED indicators	Power, LAN	...
DDNS	✓	...
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p
DHCP server	✓	...
Lens	4 mm
Mounting standard	VESA : 75, 100, 100x150, 150x150, 200x100, 200, 300x200, 300, 400x200, 400x300, 400
View angle	• 88 ° (manufacturer data) • 80 ° (our tests result)
Range of IR illumination	30 m
Screen size range	37 " ... 70 "
S/N ratio	> 52 dB
Bearing capacity	40 kg
RS-485 interface	—
Memory card slot	—
Protections	• NAT network firewall • LAN ACL • Contact/Air (ESD/EMP) : ± 24 kV / ± 24 kV	...
Distance from mounting surface	67 ... 355 mm
Image compression method	Ultra 265 / H.265 / H.264
Tilt adjustment	-15 ° ... 3 °
Alarm inputs / outputs	—
Management interface	• Software EdgeOS, Software PC • Remote management • Web browser	...
Audio	—
Horizontal rotation	-60 ° ... 60 °

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main stream frame rate	25 fps @ 1080p
Rotation in the plane of the screen	-3 ° ... 3 °
Network interface	10/100 Base-T (RJ-45)
Main features	...	DIN 934 compliance	<ul style="list-style-type: none"> • IEEE 802.1Q VLAN • PPPoE • Static routing • DHCP • IPv6 compliance • IGMP • NAT • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN • Dynamic DNS • Client - Radius support • QoS - mechanisms, which provide the high quality of transmission • Switch is managed via a web browser, command line interface and SNMP, NetFlow, LLDP, NTP, UBNT Discovery Protocol protocols • View topology and network status • RESET button • Possible power supply via Passive PoE via eth4/Poe OUT port - 24 V ("+": 4, 5 pins; "-": 7, 8 pins) • Possibility to mount to the wall 	...
Network protocols	IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP
Power supply PoE	Ubiquiti Passive PoE	...
WEB Server	Built-in
Max. number of on-line users	4
ONVIF	✓
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Operation temp	-10 °C ... 45 °C	...
Default IP address	DHCP or 192.168.1.13
Default admin user / password	admin / 123456
Permissible relative humidity	10 % ... 90 % (non-condensing)	...
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80
Port ONVIF	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Motion Detection - max. 4 zones • Privacy zones - max. 4 • Sharpness - sharper image outlines
Power supply	<ul style="list-style-type: none"> • 12 V DC / 0.5 A (power adapter included) • Passive PoE 24 V - port eth0/PoE IN 	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 410 mA
Power consumption	max. 5 W	≤ 5 W
Housing	Metal	Dome, Metal + Plastic
Color	Black	White
"Index of Protection"	IP67
Vandal-proof	—
Operation temp	-30 °C ... 60 °C
Weight	3.36 kg	0.002 kg	0.172 kg	0.28 kg
Dimensions	440 x 420 x (67 ... 355) mm	...	110 x 75 x 22 mm	Ø 118 x 95 mm
Supported languages	Polish, English
Manufacturer / Brand	BRATECK	...	UBIQUITI	UNIVIEW
Guarantee	2 years	2 years	2 years	3 years