




	ELECTRIC CABLE DY-2.5-BN/750V	DOUBLE-SIDED MARKER MARKER/0.5-1.0/BLACK	ACCESS CONTROLLER ASC2204B-S DAHUA
			
	0.39 EUR 0.39 EUR	0.76 EUR 0.76 EUR	286.62 EUR 286.62 EUR
Number of served transitions	4 (one-way)
Support	DAHUA
Number of supported readers	4 pcs
In section	100 m . Price for 1m when buying a whole roll
Battery backup support	—
Inner conductor	2.5 mm ² - Cu wire
Output lines	5 pcs - Relay
Rated voltage	450 / 750 V
Application	...	Any surface : Wood, Fabric, Glass, Metal, Plastic, Ceramics, CD/DVD discs	...
Outer coating	Ø 3.3 mm - PVC
Coating color	Brown
Communication	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand
Power supply	12 V DC / 1.4 A
Ink color	...	Black	...
Main features	...	<ul style="list-style-type: none"> • high quality • 2 line thicknesses, • round tips : 0.5 mm, 1 mm • waterproof permanent ink 	<ul style="list-style-type: none"> • 100000 indexed users • History of 150000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress
Default IP address	192.168.0.2

Default admin user / password	admin / - The administrator password should be set at the first start
Operation temp	-30 °C ... 60 °C
Permissible relative humidity	max. 95 % (non-condensing)
Weight	0.354 kg
Dimensions	...	141 x 15 x 11 mm	207 x 116 x 52 mm
Manufacturer / Brand	DAHUA
Guarantee	2 years	...	3 years