



	<a href="#">ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT APTI-AI71FRTD 4.5 mm - 1080p</a>	<a href="#">ACCESS POINT RG-RAP6262 Wi-Fi 6 2.4 GHz, 5 GHz 574 Mbps + 2402 Mbps REYEE</a>
		
	240.00 PLN 240.00 PLN	1369.00 PLN 1369.00 PLN
Frequency range	...	2.4 GHz, 5 GHz
Scanning system	Progressive	...
Optical zoom	—	...
Antenna type	...	2x2 MU-MIMO, 2.4 GHz - 3 dBi / 5.0 GHz - 4 dBi, Integrated - 5 x Omnidirectional antenna
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS 1/5 " GC2145	...
Standards	...	IEEE 802.11 a/b/g/n/ac/ax
Matrix size	2.1 Mpx 2 Mpx	...
Pixel pitch	1.75 μm	...
Lens	4.5 mm 2.4 mm	...
View angle	68 ° 70 °	...
Resolution	1920 x 1080 - 1080p 800 x 600 - 0.48 Mpx	...
Standard	TCP/IP	...
Range of IR illumination	5 m	...
White light LED illuminator range	5 m	...
Baud rates	...	2.4 GHz : max. 574 Mbps + 5 GHz : max. 2402 Mbps
Temperature measurement	✓	...
Temperature measurement range	35 °C ... 42 °C	...
Accuracy of temperature measurement	± 0.3 °C	...
Face recognition distance	0.5 m ... 2.3 m (max 30 000 faces in the database)	...
Temperature measurement distance	0.5 m ... 1.3 m optimal distance : 0.75 m	...

Internal memory	Support storage of 25 000 records	...
Video output	—	...
RS-485 interface	✓	...
Wiegand interface	✓	...
Memory card slot	—	...
Alarm inputs / outputs	0 / 2 ( bolt control, signaling of exceeding the temperature )	...
Relay output	NO, NC	...
Audio	Speaker built-in	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4, HTTP, HTTPS, TCP/IP	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	—	...
RS-485	✓	...
Protections	...	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK
Default admin user / password	admin / 12345	...
LAN ports	...	1 x 10/100/1000 Mbps 1 x 1000 Base-X port SFP
Web browser access ports	7080	...
PC client access ports	7080	...
Mobile phones support	...	Android: Free application <a href="#">Ruijie Reyee</a> iOS (iPhone): Free application <a href="#">Ruijie Reyee</a>
Management interface	...	Web browser, Ruijie Cloud
Default IP address	DHCP / 192.168.1.88	10.44.77.253
Main features	<ul style="list-style-type: none"> <li>• Built-in LCD display showing the image from the video camera and the result of temperature measurement - 1024 x 600 px</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• RESET button</li> <li>• Wiegand 26</li> <li>• Relay output operating modes: access control or notification of an exception</li> </ul>	...
Transmitter power	...	≤ 32 dBm @ 2.4 GHz ≤ 34.7 dBm @ 5 GHz

Housing	Compact - Metal	Outdoor, plastic (Weatherproof)
Color	Silver	...
Overvoltage protection	...	4 kV lightning
Power supply PoE	...	✓
Operation temp	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)	...
Power supply	12 V DC	• PoE (802.3at) • 12 V / 2 A (power adapter not included)
Power consumption	≤ 12 W	≤ 24 W
Operation temp	...	-30 °C ... 65 °C
Length of the cable	64 cm	...
Permissible relative humidity	...	0 % ... 100 %
Certificates	...	CE, RoHS
Supported languages	Polish, English, French, Spanish, German, Portuguese, Russian, Turkish, Italian	...

Main features	...	<ul style="list-style-type: none"> <li>• Access Point is managed through the web and the cloud (Ruijie Reyeeye application)</li> <li>• Mobile phones support</li> <li>• Number of users : 512 (max)</li> <li>• Multi-SSID ( max. 8 )</li> <li>• Enable/Disable Wireless Radio</li> <li>• WMM (Wi-Fi Multimedia)</li> <li>• Transmit power control</li> <li>• Support for Reyeeye Mesh technology</li> <li>• Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source</li> <li>• Load balance</li> <li>• Rate limit</li> <li>• Wireless Network Schedule</li> <li>• Wireless transmission statistics</li> <li>• Access control</li> <li>• MAC addresses filtering</li> <li>• Wireless isolation between clients</li> <li>• SSID to VLAN mapping</li> <li>• Remote management</li> <li>• RESET button</li> <li>• LED indication</li> <li>• Power supply PoE</li> <li>• Easy to install on any wall or pole (mounting kit included)</li> </ul>
"Index of Protection"	IP66	IP68
Weight	0.76 kg	2.67 kg (without mounting kit)
Dimensions	112 x 220 x 41 mm (with bracket)	395 x 230 x 195 mm (without mounting kit)
Pole diameters range	...	Ø 70 ... Ø 140 mm
Manufacturer / Brand	APTI	RUIJIE / REYEYE
Guarantee	3 years	3 years