



	<a href="#">IP CAMERA IPC3615SB-ADF28KMC-I0 Tri-Guard - 5 Mpx 2.8 mm UNIVIEW</a>	<a href="#">IP CAMERA DS-2CD2387G2P-LSU/SL(4MM)(C)/BLACK PANORAMIC ColorVu - 7.4 Mpx 2 x 4 mm Hikvision</a>
		
	1325.61 PLN 1325.61 PLN	2544.00 PLN 2544.00 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/2.7 " Progressive Scan CMOS	2 x 1/1.8 " Progressive Scan CMOS
Matrix size	5 Mpx	2 x 3.7 Mpx - 8 Mpx (total)
Scanning system	...	Progressive
Resolution	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	5120 x 1440 - 7.4 Mpx
Lens	2.8 mm	2 x 4 mm
View angle	• 101 ° (manufacturer data) • 105 ° (our tests result)	180 ° (horizontal) 44 ° (vertical)
White light LED illuminator range	30 m	30 m
Range of IR illumination	30 m	...
S/N ratio	> 56 dB	...
RS-485 interface	—	—
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	—	1 / 1
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Speaker built-in</li> <li>• Audio transmission via network</li> <li>• Audio detection</li> </ul>	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• External microphone input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Digital Noise Reduction</li> </ul>
Main stream frame rate	25 fps @ 5 Mpx	20 fps @ 7.4 Mpx
Network interface	10/100 Base-TX (RJ-45)	10/100 Base-T (RJ-45)
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>
Default IP address	DHCP or 192.168.1.13	192.168.1.64
Default admin user / password	admin / 123456	admin / - The administrator password should be set at the first start
Web browser access ports	80, 554	80
WEB Server	Built-in	Built-in

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Max. number of on-line users	32	6
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
ONVIF	✓	✓
Mobile client access ports	80	8000
Port ONVIF	80	80
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• Active deterrence function - Light and sound alarm</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Auto White Balance</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Sharpness - sharper image outlines</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, people counting, crowd gathering estimation, face detection</li> <li>• Overvoltage protection : 4 kV</li> </ul>	<ul style="list-style-type: none"> <li>• Intelligent image analysis - crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, scene changing</li> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• NAS - Network Attached Storage support</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• Active deterrence function - Light and sound alarm</li> <li>• White light (LED) illuminator built-in : 4 LEDs</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• AGC - Automatic Gain Control</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Configurable: brightness, contrast, saturation</li> <li>• Motion Detection - classification of people and vehicles</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 625 mA</li> </ul>	<ul style="list-style-type: none"> <li>• 12 V DC / 790 mA,</li> <li>• PoE (802.3af)</li> </ul>
Power consumption	≤ 7.5 W	<ul style="list-style-type: none"> <li>• ≤ 9.5 W @ 12 V DC</li> <li>• ≤ 10.5 W @ PoE</li> </ul>
Housing	Dome, Metal	Compact, Metal
Color	White	Black

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel.:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

"Index of Protection"	IP67	IP67
Vandal-proof	—	—
Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C
Weight	0.42 kg	1.28 kg
Dimensions	Ø 110 x 95 mm	Ø 156 x 155.3 mm
Supported languages	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
SAP Code	...	311323800
Manufacturer / Brand	UNIVIEW	Hikvision
Guarantee	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00