

	IP CAMERA BCS-L-TIP55VSR6-A11 - 5 Mpx 2.7 ... 13.5 mm - MOTOZOOM BCS Line	IP CAMERA BCS-L-EIP55FCR3L3-A11-G(2) - 5 Mpx 2.8 mm BCS Line	CONNECTOR STRIP KE-CPG-5A-IP SIMET
			
	1995.00 PLN 1995.00 PLN	1589.00 PLN 1589.00 PLN	3.01 PLN 3.01 PLN
Number of terminal pairs	1
Standard	TCP/IP	TCP/IP	
Connector type	terminals
Nominal voltage	450 V
Sensor	1/2.7 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	...
Rated current	32 A
Matrix size	5 Mpx	5 Mpx	...
Wire gauge	4 mm ²
Dielectric	Porcelain
Resolution	2960 x 1668 - 5 Mpx , 2880 x 1620 - 4.7 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	2960 x 1688 - 5 Mpx , 2880 x 1620 - 4.7 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3.1 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Lens	2.7 ... 13.5 mm - Motozoom	2.8 mm	...
View angle	• 99 ° ... 28 ° (manufacturer data) • 106 ° ... 34 ° (our tests result)	• 97 ° (manufacturer data) • 104 ° (our tests result)	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG / AI Coding	...
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG / AI Coding
Range of IR illumination	60 m	30 m	...
Alarm inputs / outputs	1 / 1	1 / 1	...
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	...
Audio	• External microphone input • Audio output • Bi-directional audio streaming support • Audio detection	• Microphone built-in • Audio transmission via network • Compliance with the AAC standard	...
WEB Server	Built-in	Built-in	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 256GB support (possible local recording)	...
Max. number of on-line users	20	20	...
ONVIF	✓	21.12	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager	Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager	...
Default IP address	192.168.1.108	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start	...
Main stream frame rate	• 20 fps - 5 Mpx • 25 fps - 4 Mpx	25 fps @ 8.3 Mpx	...
Web browser access ports	80, 37777	80, 37777	...
PC client access ports	37777	37777	...
Mobile client access ports	37777	37777	...
Port ONVIF	80	80	...
RTSP URL	• Main stream : rtsp://admin.haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 • Sub stream : rtsp://admin.haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1	rtsp://admin.haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin.haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
RS-485 interface	-	-	...
Main features	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Configurable Privacy Zones • Intelligent image analysis : intrusion, crossing the line (tripwire), Smart motion detection (with recognizing people and vehicles)	• Motozoom lens - Controlling from browser, NVR or software • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode (color/b&w/auto) • ICR - Movable InfraRed filter • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • Audio detection • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, scene changing	...
Power supply	• PoE (802.3af), • 12 V DC / 820 mA	• PoE (802.3af), • 12 V DC / 730 mA	...
Vandal-proof	...	-	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power consumption	<ul style="list-style-type: none"> • ≤ 8.5 W @ PoE (802.3at) • ≤ 7.4 W @ 12 V DC 	≤ 8.8 W	...
Housing	Compact, Metal	Dome - Metal	...
Color	White	Graphite	White
"Index of Protection"	IP67	IP67	...
Operation temp	-30 °C ... 60 °C	-40 °C ... 60 °C	...
Supported languages	Polish, English	Polish, English	...
Weight	0.74 kg	0.75 kg	...
Dimensions	244 x 79 x 76 mm	Ø 122 x 108 mm	16 x 18 x 12 mm
Manufacturer / Brand	BCS Line	BCS Line	SIMET
Guarantee	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00