

	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA25FSR3-G(H2) - 5 Mpx 2.8 mm	CABLE MANAGER TRSS-6*P200	AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA HAC-HDW1800M-0280B - 8.3 Mpx 2.8 mm DAHUA
			
	190.00 PLN 190.00 PLN	88.00 PLN 88.00 PLN	394.00 PLN 394.00 PLN
Standard	AHD / HD-CVI / HD-TVI / CVBS	...	AHD / HD-CVI / HD-TVI / CVBS
In package	...	200 pcs The price for package	...
Matrix size	8.3 Mpx
Number of holes	...	1 pcs for cable diameter max. Ø 7 mm	...
Assembly	...	The bottom layer is equipped with a Scotch tape	...
Material	...	Plastic	...
Sensor	1/2.8 " STARVIS™ CMOS	...	1/2.7 " CMOS
Resolution	<ul style="list-style-type: none"> • 2704 x 1950 - 5 Mpx @ AHD / HD-TVI - 20 fps • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI - 25 fps • 960 x 576 - 960H @ PAL 	...	3840 x 2160 - 8.3 Mpx @ HD-CVI @ 25 fps , 3840 x 2160 - 8.3 Mpx @ HD-CVI / HD-TVI / AHD @ 15 fps , 2592 x 1944 - 5 Mpx @ HD-CVI @ 20 fps , 2560 x 1440 - 3.7 Mpx @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Range of IR illumination	30 m	...	30 m
IR illuminator power adjustment	Automatic
Lens	2.8 mm	...	2.8 mm
View angle	103 °	...	<ul style="list-style-type: none"> • 105 ° (manufacturer data) • 101 ° (our tests result)
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio output 	...	—
Mechanical protection class	—

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • Auto White Balance • AGC - Automatic Gain Control • 3D-DNR - Digital Noise Reduction • Day/night mode • ICR - Movable InfraRed filter 	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Mirror - Mirror image • Auto White Balance • Configurable Privacy Zones • Sharpness - sharper image outlines
OSD menu	✓	...	OSD menu available via DAHUA recorder
Supported languages	Polish, English
Power supply	12 V DC / 416 mA	...	12 V DC / 360 mA
Power consumption	< 5 W	...	≤ 4.3 W
Housing	Dome, Metal	...	Dome, Metal
Color	Graphite	Transparent	White
"Index of Protection"	IP66	...	IP67
Vandal-proof	—
Operation temp	-20 °C ... 60 °C	...	-40 °C ... 60 °C
Weight	0.3 kg	...	0.29 kg
Dimensions	Ø 94 x 80 mm	31 x 11 x 11 mm	Ø 93 x 79 mm
Manufacturer / Brand	BCS UNIVERSAL	...	DAHUA
Guarantee	3 years	2 years	3 years