

	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR BCS-L-XVR0801(6) 8 CHANNELS BCS Line	Switch RG-NBS5100-24GT4SFP 24-PORT REYEE
		
	935.00 PLN 935.00 PLN	1665.00 PLN 1665.00 PLN
LAN ports	...	<ul style="list-style-type: none"> • 24 x (RJ45) 10/100/1000 Mbps • 4 x SFP ports
Management	...	✓
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...
Video inputs	8 pcs BNC	...
Transmission speed	...	10/100/1000 Mbps - 24 x Gigabit Ethernet 1000 Mbps - 4 x port SFP
Video outputs	1 pcs HDMI 1 pcs VGA	...
Switching capacity	...	56 Gb/s
Audio inputs	1 pcs CINCH	...
Forwarding rate	...	42 Mpps
Audio outputs	1 pcs CINCH	...
MAC addresses table	...	16k
Certificates	...	CE, RoHS
Number of fan coolers	...	1
Image compression method	AI Coding / H.265+ / H.265 / H.264+ / H.264	...
Jumbo Frame	...	9 kB
Default IP address	...	10.44.77.200

Main features	...	<ul style="list-style-type: none"> • Can be mounted in a Rack cabinet • Switch is managed through the web and the cloud (Ruijie Reeye application) • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • DHCP client • BPDU Filtering/Guard • Loop back detection • Spanning Tree STP/RSTP • Errdisable Recovery • Up to 16 aggregation groups and up to 8 ports per group • IGMP Snooping V1/V2/V3 • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Protections	...	Protection against lightning discharges : 6 kV
Image records resolutions	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 5 Mpx - 2560 x 1944 px 1,2,3,4 CH only , 5M-N - 1296 x 1440 px , 4M-N - 1280 x 1440 px , 1080p - 1920 x 1080 px , 1080N - 960 x 1080 px , 720p - 1280 x 720 px , • CVBS : 960H - 960 x 576 px • IP : max. 6 Mpx - 3072 x 2048 px 	...



Recording speed adjustment	6 Mpx IP @ 1 ... 25 fps 5 Mpx @ 1 ... 6 fps 1,2,3,4 CH only 5M-N @ 1 ... 12 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel	...
Operation modes	8 x AHD / HD-CVI / HD-TVI / CVBS / IP + 4 IP	...
Recording modes	Manual, Motion Detection, Schedule	...
Supported hard drives	1 x 16 TB SATA	...
External storage devices backup	Save single frames and whole records from DVR drive to the USB drive	...
Searching and playback the records	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) 1/4/9 channel synchronous playback	...
Network interface	1 x RJ-45 - 10/100 Base-TX	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters , Web-Server built-in - 128 on- line users , ONVIF	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager	Android: Free application Ruijie Reeye iOS (iPhone): Free application Ruijie Reeye
USB	2 x USB 2.0	...
Serial ports	RS-485	...
Alarm inputs / outputs	—	...

PTZ control	IP Speed Dome Cameras RS-485 - PELCO-D/P and others	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...
Intelligent image analysis	✓	...
Main features	<ul style="list-style-type: none"> • Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles • Smart motion detection (with recognizing people and vehicles) • face detection - supports 6 types of facial attributes extraction • Face recognition and analysis in real time (up to 8 photos per second) • Support for up to 10 face databases, including 10 000 face images • Cooperation with POS (Point of Sale) terminals • SMD PLUS - searching for an object classified as: human, motor vehicle • Privacy zones - max. 4 	...
Mouse support	✓	...
IR remote controller in the set	—	...
Power supply	12 V DC / 2 A (power adapter included)	100 V ... 240 AC
Power consumption	max. 7 W (without HDD)	≤ 28 W
Color	Black	...
Weight	0.9 kg	2.84 kg
Dimensions	260 x 235 x 47 mm	440 x 207 x 44 mm
Supported languages	Polish, English	...
Manufacturer / Brand	BCS Line	RUIJIE / REYEE
Guarantee	3 years	5 years