




	<a href="#">IP CAMERA DS-2CD1343G0-I(2.8MM)(C) - 4 Mpx Hikvision</a>	<a href="#">UNIVERSAL METER UT-52 UNI-T</a>	<a href="#">SWITCHING ADAPTER WITH SEPARATOR M-SEP/HDR-30-24 VIDOS</a>
			
	1741.35 SEK 1741.35 SEK	282.56 SEK 282.56 SEK	509.79 SEK 509.79 SEK
Standard	TCP/IP	...	...
Compatibility	...	...	VIDOS DUO
Sensor	1/3 " Progressive Scan CMOS	...	...
Adapter type	...	...	Switching
Scanning system	Progressive	...	...
Matrix size	4 Mpx	...	...
Power voltage	...	...	85 ... 264 V AC
Output voltage	...	...	24 V DC
Output voltage adjustment	...	...	21.6 ... 29 V
Maximal load	...	...	1.5 A
Output power	...	...	36 W
Number of outputs	...	...	4 pcs
Housing type	...	...	DIN
Vibration resistance	...	...	✓
Resolution	2560 x 1440 - 4 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...	...
Lens	2.8 mm	...	...
Protections	...	...	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overload</li> <li>• Overvoltage</li> </ul>
View angle	<ul style="list-style-type: none"> <li>• 98 ° (manufacturer data)</li> <li>• 95 ° (our tests result)</li> </ul>	...	...
Operation temp	...	...	-10 °C ... 50 °C
Range of IR illumination	30 m	...	...
DC voltage measurement	...	200 mV ± (0.5% + 1) @ 0.1 mV, 2 V ± (0.5% + 1) @ 0.001 V , 20 V ± (0.5% + 1) @ 0.01 V , 200 V ± (0.5% + 1) @ 0.1 V , 1000 V ± (0.8% + 2) @ 1 V	...
Memory card slot	—	...	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...
Alarm inputs / outputs	—	...	...
Audio	—	...	...
Main stream frame rate	<ul style="list-style-type: none"> <li>• 20 fps @ 4 Mpx</li> <li>• 25 fps @ 3 Mpx</li> </ul>	...	...
Network interface	10/100 Base-T (RJ-45)	...	...

AC voltage measurement	...	200 mV ± (1.2% + 3) @ 0.1 mV, 2 V ± (0.8% + 3) @ 0.001 V, 20 V ± (0.8% + 3) @ 0.01 V, 200 V ± (0.8% + 3) @ 0.1 V, 750 V ± (1.2% + 3) @ 1 V	...
DC current measurement	...	2 mA ± (0.8% + 1) @ 0.001 mA, 20 mA ± (0.8% + 1) @ 0.01 mA, 200 mA ± (1.5% + 1) @ 0.1 mA, 20 A ± (2.0% + 5) @ 0.01 A	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv4, IPv6, UDP, Bonjour, UDP, SSL / TLS	...	...
WEB Server	Built-in	...	...
Max. number of on-line users	6	...	...
ONVIF	18.12	...	...
AC current measurement	...	2 mA ± (1.0% + 3) @ 0.001 mA, 20 mA ± (1.0% + 3) @ 0.01 mA, 200 mA ± (1.8% + 3) @ 0.1 mA, 20 A ± (3.0% + 7) @ 0.01 A	...
Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• BLC - Back Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Motion Detection</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> </ul>	...	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>	...	...
Default IP address	192.168.1.64	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	80	...	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...	...
Mobile client access ports	8000	...	...
Port ONVIF	80	...	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RTSP URL	<ul style="list-style-type: none"> <li>Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li> <li>Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li> </ul>	...	...
Resistance measurement	...	<p>200 Ω ± (0.8% + 3) @ 0.1 Ω , 2 kΩ ± (0.8% + 1) @ 0.001 kΩ , 20 kΩ ± (0.8% + 1) @ 0.01 kΩ , 200 kΩ ± (0.8% + 1) @ 0.1 kΩ , 2 MΩ ± (0.8% + 1) @ 0.001 MΩ 20 MΩ ± (1.0% + 2) @ 0.01 MΩ , 200 MΩ ± (5%(RD-10) + 10) @ 0.1 MΩ *</p> <p>*RD - reading value</p>	...
Power consumption	<p>≤ 6.5 W @ PoE ≤ 5 W @ 12 V DC</p>	...	...
Housing	Dome, Metal + Plastic	...	...
Color	White	...	...
"Index of Protection"	IP67	...	...
Vandal-proof	—	...	...
Operation temp	-30 °C ... 60 °C	...	...
Capacitance measurement	...	<p>2 nF ± (4% + 3) @ 0.001 nF , 20 nF ± (4% + 3) @ 0.01 nF , 200 nF ± (4% + 3) @ 0.1 nF ... 2 μF ± (4% + 3) @ 0.001 μF , 20 μF ± (4% + 3) @ 0.01 μF</p>	...
Inductance measurement	...	—	...
Frequency measurement	...	—	...
Temperature measurement	...	—	...
Automatic change of measuring ranges	...	—	...
hFE	...	✓	...
Diode test	...	✓	...
Sound signal of the continuity test	...	✓	...
Checking TTL logic states	...	—	...
RS-232	...	—	...
Main features	...	<ul style="list-style-type: none"> <li>Large, readable LCD display</li> <li>Low battery level alarm</li> <li>Aesthetic and solid construction</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>PoE (802.3af),</li> <li>12 V DC / 420 mA</li> </ul>	9V, type 6F22 battery - included	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Weight	0.33 kg	0.5 kg	0.33 kg
Dimensions	Ø 110 x 85 mm	203 x 98 x 56 mm	70 x 98 x 59 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian	...	...
Manufacturer / Brand	Hikvision	UNI-T	VIDOS
SAP Code	311315731	...	...
Guarantee	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00