



	NVR NVR4116HS-4KS3 16 CHANNELS DAHUA	HDMI DOUBLE SOCKET DGHDMI2.01/49-SIMON54
		
	1160.00 PLN 1160.00 PLN	194.72 PLN 194.72 PLN
Standard	TCP/IP	...
Mount	...	Flush-mounted, Claw or screw mounting
Sockets type	...	2 pcs HDMI 1.4
Supported resolutions	max. 12 Mpx - 4000 x 3000 px	...
Connector	...	2 pcs HDMI socket
Video outputs	1 pcs HDMI 4K 1 pcs VGA	...
Application	...	Simon 54 product series, for Nature, Premium frames
Housing	...	Non-halogen plastic, PC
Audio support	<ul style="list-style-type: none"> • 16 Channels - Audio from cameras • Bi-directional audio streaming support 	...
Color	...	Matt black
Audio inputs	1 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Image compression method	Smart H.265+ / H.265 / Smart H.264+ / H.264	...
Bitrate	max. 160 Mbps (without AI) max. 80 Mbps (AI)	...
Supported hard drives	1 x 20 TB SATA	...
Recording modes	Manual, Motion Detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	<ul style="list-style-type: none"> • Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Smart Playback function • Records playback from max. 4 channels in the same time 	...
Network interface	1 x RJ-45 10/100/1000 Base-TX	...
Network functions	Full support via network, Remote records copying, Web-Server built-in	...
Network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UDP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, FTP, DDNS, SNMP, Alarm Server, P2P, Auto Register, IP Search	...
ONVIF	22.12	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / admin The administrator password should be set at the first start	...

Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
RTSP URL	<ul style="list-style-type: none"> • rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream • rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream 	...
USB	2 pcs USB 2.0	...
Serial ports	—	...
Alarm inputs / outputs	—	...
PTZ control	IP Speed Dome Cameras	...
Motion Detection	✓	...
Intelligent image analysis	✓	...
Main features	<ul style="list-style-type: none"> • SMD PLUS - searching for an object classified as: human, motor vehicle • Filtering of false alarms based on the recognition of persons and vehicles • Privacy zones Functions implemented in cooperation between the recorder and cameras that support these functions : <ul style="list-style-type: none"> • Intelligent image analysis : perimeter protection, scene changing • face detection - supports 6 types of facial attributes extraction • Face recognition • people counting • heat map 	...
Mouse support	✓	...
IR remote controller in the set	—	...
Switch PoE	—	...
Power supply	12 V DC / 2 A (power adapter included)	...
Power consumption	max. 10 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.81 kg	0.052 kg
Dimensions	260 x 233 x 48 mm	<ul style="list-style-type: none"> • 75 x 75 x 33 mm • 22 mm - mounting depth
Supported languages	Polish, English	...
Manufacturer / Brand	DAHUA	KONTAKT Simon
Guarantee	3 years	6 years