

	VIDEO SEPARATOR SV-1000P STANDARD: PAL,	GROUNDING RESISTANCE METER UT-522 UNI-T
		
	141.29 PLN 141.29 PLN	819.65 PLN 819.65 PLN
Standard	CVBS - PAL / NTSC	...
Number of inputs	1 pcs BNC	...
Number of outputs	1 pcs BNC	...
Input impedance	75 Ω	...
Output impedance	75 Ω	...
Galvanic (optical) isolation between signal inputs and outputs	1000 V peak	...
Opto-isolation between power and signal inputs / outputs	1000 V peak	...
Gain adjustment	-5 dB ... +5 dB	...
Bandwidth	9 MHz / 1 Vpp	...
Transmission error	0.75 % (f=3.58MHz, Vin=1Vpp)	...
Assembly	To the wall	...
Resistance measurement	...	40 Ω ± (2% + 20) @ 0.01 Ω , 400 Ω ± (2% + 3) @ 0.1 Ω , 4000 Ω ± (2% + 3) @ 1 Ω • Auxiliary resistance : 500 Ω ± 5 % • Measuring voltage : ≤ 10 V AC @ ~820 Hz
Ground voltage measurement	...	400 V ± (1.0% + 6) @ 1 V
Automatic change of measuring ranges	...	—
RS-232	...	—
USB	...	—

Main features	...	<ul style="list-style-type: none"> • Hold - stopping the meter reading, • The measurement can be performed in full or simplified configuration, • Warning of poor connection of leads during measurement, • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction, • The set includes a practical case
Operation temp	...	5 °C ... 40 °C
Permissible relative humidity	...	≤ 80 % (non-condensing)
Power supply	12 V DC / 80 mA	6 x 1.5V, type AA/LR6/FR6 battery - included
Weight	0.095 kg	0.42 kg
Dimensions	61 x 120 x 30 mm	160 x 100 x 70 mm
Manufacturer / Brand	DELTA	UNI-T
Guarantee	3 years	2 years