




	MULTIPURPOSE WIRELESS DETECTOR MXD-300-BR SATEL	SCREWDRIVER SET WH-SFE/PACK-2/7/SLIMFIX WIHA	DUAL SMART SWITCH SWITCHBOX-D/BLEBOX Wi-Fi, 230 V AC
			
	221.05 DKK 221.05 DKK	505.80 DKK 505.80 DKK	278.44 DKK 278.44 DKK
Application	switching devices on/off
Rated voltage	230 V AC
Number of screwdrivers	...	5 pcs	...
Maximal total load	2 x 1150 W / 1150 VA
Detection	<ul style="list-style-type: none"> • Opening the door or window, • Shocks, Vibrations, • Water
Total maximal current	2 x 5 A
Number of inputs	2
Frequency band	433.05 MHz ... 434.79 MHz
Number of outputs	2
Connector type	screw terminals
Bits sizes	...	Philips : PH1, PH2 , Standard/Slotted : 3.5 mm, 4,5 mm, 5.5 mm	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
Max. diameter of the wire	...	Ø 2 mm	...
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS
Length	...	165 mm	...
Radio communication range (at open area)	<ul style="list-style-type: none"> ≤ 600 m - PERFECTA ≤ 500 m - VERSA-MCU / MTX-300 / MICRA ≤ 300 m - MRU-300
Support	Satel MICRA
Voltage insulation	...	1000 V	...
Alarm signaling	<ul style="list-style-type: none"> • Signal to control panel • LED indicator
Tamper contact	✓
Battery	CR123A 3 V (included)
Backup time	max. 2 years
Current consumption	≤ 22 mA
Protection class (Grade)	2

Environmental class EN 50130-5	II
Housing	Plastic
"Index of Protection"	IP20
Main features	<ul style="list-style-type: none"> • detecting the presence of water in spaces where there is a risk of leakage • detection of shocks and vibrations accompanying attempts to force a door or window open • detection of opening doors, windows, etc. (magnetic detector) • input for connecting a NC type wired detector • input for connecting a wired roller shutter detector • battery diagnostics • Encrypted radio communication in the 433 MHz frequency band • Tamper detection - opening the enclosure, removing from mounting surface 	<ul style="list-style-type: none"> • Insulation made in accordance with VDE • Compliance with IEC 60900 standard • GS quality mark • The set includes a practical case 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • remote access, • voice control, • The ability to set the default status of the device after a power failure, • µWiFi technology support
Operation temp	-10 °C ... 55 °C	...	-20 °C ... 50 °C
Permissible relative humidity	93 ± 3 %
Color	Brown	...	Black
Weight	0.04 kg	1.015 kg (total)	0.04 kg
Dimensions	24 x 110 x 27 mm	...	41 x 39 x 23 mm
Manufacturer / Brand	SATEL	WIHA	BleBox
Guarantee	2 years	2 years	2 years