


	NVR DS-9664NI-I8 64 CHANNELS Hikvision
	
	11665.58 PLN 11665.58 PLN
Standard	TCP/IP
Supported resolutions	max. 12 Mpx - 4000 x 3000 px
Video outputs	2 pcs HDMI 2 pcs VGA Simultaneous image display for VGA1/HDMI1 and VGA2/HDMI2, Possibility to configure one pair of outputs as SPOT output
Audio support	<ul style="list-style-type: none"> • 64 Channels - Audio from cameras • Bi-directional audio streaming support
Audio inputs	1 pcs CINCH
Audio outputs	2 pcs CINCH
Image compression method	H.265 / H.265+ / H.264 / H.264+ / MPEG-4 / MJPEG
Supported hard drives	8 x 10 TB SATA + eSATA , SINGLE, Raid 0/1/5/6/10
Recording modes	Manual, Sensor, Motion detection, Schedule
Network protocols	TCP/IP, UDP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTP, HTTPS, SMTP, RTP, FTP, SNMP, ONVIF
External storage devices backup	Backup to USB drive (pendrive, external drive)
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function Records playback from max. 16 channels in the same time @ 1080p or max. 2 @ 12 Mpx
Bitrate	max. 320 Mbps (200 Mbps in RAID configuration)
Network functions	<ul style="list-style-type: none"> • Live image view, Playback the records, Backup the records • max. 128 on-line users - iVMS-4200 application • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Operation modes : Normal / Hot Spare
ONVIF	✓
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) Android: Free application iVMS-4500 or Hik-Connect iOS (iPhone): Free application iVMS-4500 or Hik-Connect
Default IP address	192.168.1.64
Default admin user / password	admin / -
Web browser access ports	80, 8000
PC client access ports	8000

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	8000
RTSP URL	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
USB	<ul style="list-style-type: none"> • 2 pcs USB 2.0 • 1 pcs USB 3.0
Alarm inputs / outputs	16 / 4
PTZ control	✓
Motion Detection	22 x 18 motion zones
Intelligent image analysis	✓
Mouse support	✓
IR remote controller in the set	—
Main features	Possibility of operation the disks in RAID 0/1/5/6/10 array
Power supply	100 V ... 240 V AC
Weight	8.69 kg
Dimensions	445 x 470 x 90 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Country of origin	China
Manufacturer / Brand	Hikvision
SAP Code	303602764
Guarantee	3 years