



	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1500CLO-IL-A-0280B-S2 - 5 Mpx 2.8 mm DAHUA	AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA HAC-HDW1800M-0280B - 8.3 Mpx 2.8 mm DAHUA
		
	324.00 PLN 324.00 PLN	394.00 PLN 394.00 PLN
Standard	AHD, HD-CVI, HD-TVI, CVBS	AHD / HD-CVI / HD-TVI / CVBS
Sensor	Progressive Scan CMOS	1/2.7 " CMOS
Matrix size	5 Mpx	8.3 Mpx
Resolution	2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps - Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx @ HD-CVI / HD-TVI / AHD @ 25 fps , 1920 x 1080 - 1080p @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	3840 x 2160 - 8.3 Mpx @ HD-CVI @ 25 fps , 3840 x 2160 - 8.3 Mpx @ HD-CVI / HD-TVI / AHD @ 15 fps , 2592 x 1944 - 5 Mpx @ HD-CVI @ 20 fps , 2560 x 1440 - 3.7 Mpx @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Range of IR illumination	20 m	30 m
White light LED illuminator range	20 m	---
Lens	2.8 mm	2.8 mm
IR illuminator power adjustment	Automatic	Automatic
View angle	• 106 ° (manufacturer data) • 100 ° (our tests result)	• 105 ° (manufacturer data) • 101 ° (our tests result)
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only	—
OSD menu	✓	OSD menu available via DAHUA recorder

Main features	<ul style="list-style-type: none"> • Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • Auto White Balance • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • Privacy zones - max. 8 • Mirror - Mirror image • Sharpness - sharper image outlines 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Mirror - Mirror image • Auto White Balance • Configurable Privacy Zones • Sharpness - sharper image outlines
Power supply	12 V DC / 380 mA	12 V DC / 360 mA
Power consumption	≤ 4.5 W	≤ 4.3 W
Housing	Dome, Plastic	Dome, Metal
Color	White	White
"Index of Protection"	IP67	IP67
Vandal-proof	—	—
Operation temp	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.21 kg	0.29 kg
Dimensions	Ø 97 x 94 mm	Ø 93 x 79 mm
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	3 years	3 years