




| | ADAPTER AD-UTP-2W/2G 2 x RJ45 | IP CAMERA IPC-HDW3249H-AS-PV-0360B TiOC Full-Color - 1080p 3.6 mm DAHUA | FLUSH BOX 2-GANG SE-2X60-G SIMET |
|-----------------------------------|---|--|--|
| |  |  |  |
| | 23.20 PLN 23.20 PLN | 1087.00 PLN 1087.00 PLN | 38.47 PLN 38.47 PLN |
| Standard | ... | TCP/IP | ... |
| Sensor | ... | 1/2.8 " Progressive Scan CMOS | ... |
| Number of sections | ... | ... | 2 |
| Matrix size | ... | 2.1 Mpx | ... |
| Connectors type | <ul style="list-style-type: none"> • 1 Adapter : 2 x RJ-45 plug + 1 x RJ-45 socket • 2 Adapter : 3 x RJ-45 socket | ... | ... |
| Length of the cable | 3 cm | ... | ... |
| Resolution | ... | 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p | ... |
| Scanning system | ... | Progressive | ... |
| Lens | ... | 3.6 mm | ... |
| Main features | ... | ... | <ul style="list-style-type: none"> • Flush-mounted, serial, deep, for special electrical and electronic equipment • The ability to combine boxes • flammability index : 960 °C • 4 fixing points • 2 Mounting screws - included • Guides for attaching the TS35 rail |
| Material | ... | ... | halogen free and inflammable |
| View angle | ... | <ul style="list-style-type: none"> • 84 ° (manufacturer data) • 80 ° (our tests result) | ... |
| White light LED illuminator range | ... | ≤ 30 m | ... |
| Mounting holes distance | ... | ... | 60 mm |
| Min. illumination | ... | 0.0015 Lux / F1.0 (color) | ... |
| S/N ratio | ... | > 56 dB | ... |
| RS-485 interface | ... | — | ... |
| Memory card slot | ... | Micro SD memory cards up to 256GB support (possible local recording) | ... |
| Image compression method | ... | H.265+ / H.265 / H.264+ / H.264 / MJPEG | ... |
| Alarm inputs / outputs | ... | 1 / 1 | ... |
| Audio | ... | <ul style="list-style-type: none"> • Microphone built-in, • External microphone input, • Audio output, • Speaker built-in, • Bi-directional audio streaming support, • Audio detection | ... |
| Main stream frame rate | ... | 25 fps @ 1080p | ... |
| Network interface | ... | 10/100 Base-T (RJ-45) | ... |
| Network protocols | ... | IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP | ... |
| WEB Server | ... | Built-in | ... |
| Max. number of on-line users | ... | 20 | ... |
| ONVIF | ... | 20.06 | ... |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

| | | | |
|-------------------------------|--|---|------------------|
| Mobile phones support | ... | Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS | ... |
| Default IP address | ... | 192.168.1.108 | ... |
| Default admin user / password | ... | admin / - The administrator password should be set at the first start | ... |
| Web browser access ports | ... | 80, 37777 | ... |
| PC client access ports | ... | 37777 | ... |
| Mobile client access ports | ... | 37777 | ... |
| Port ONVIF | ... | 80 | ... |
| RTSP URL | ... | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream | ... |
| Main features | ... | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • SSA - Smart Scene Adaptive - intelligent scene adaptation by automatically adjusting the exposure parameters to obtain a better image • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Day/Night mode (color/b&w/auto) • Full Color - colorful night mode • Auto White Balance • AGC - Automatic Gain Control • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • Light and sound alarm • Active deterrence function • White light (LED) illuminator built-in • SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, scene changing, Audio detection | ... |
| Power supply | ... | • PoE (802.3af), • 12 V DC / 510 mA | ... |
| Power consumption | ... | • max. 7.35 W @ PoE • max. 6.1 W @ 12 V | ... |
| Housing | ... | Dome - Metal | ... |
| Color | ... | White + Black | Blue |
| "Index of Protection" | ... | IP67 | IP20 |
| Vandal-proof | ... | — | ... |
| Operation temp | ... | -40 °C ... 60 °C | ... |
| Weight | 0.05 kg (total) | 0.74 kg | 0.065 kg |
| Dimensions | <ul style="list-style-type: none"> • 1 Adapter : 115 x 19 x 19 mm • 2 Adapter : 120 x 40 | Ø 122 x 111 mm | 153 x 82 x 82 mm |
| Supported languages | ... | Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Ukrainian, Hungarian, Italian | ... |
| Manufacturer / Brand | ... | DAHUA | SIMET |
| Guarantee | 2 years | 3 years | 2 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00