



	ACCESS CONTROLLER MC16-PAC-ST-2-KIT ROGER	ACCESS CONTROLLER WITH FACE RECOGNITION DS-K1T341AM-S - 720p Hikvision
		
	2195.00 PLN 2195.00 PLN	1999.00 PLN 1999.00 PLN
Number of served transitions	2 (two-way)	...
Sensor	...	CMOS
Number of supported readers	8	...
Matrix size	...	2 Mpx
Number of users	unlimited (purchase of the appropriate license required)	...
Resolution	...	1280 x 720 - 720p
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.	...
Cards support	...	13.56 MHz S50
Buffer memory	8 000 000 events buffer	...
Number of access zones	4	...
Face recognition distance	...	0.3 m ... 1.5 m
Number of alarm zones	4	...
Battery backup support	12 V / 20 Ah	...
Memory	...	<ul style="list-style-type: none"> • Memory of 1500 face templates • Memory of 1500 RFID cards • Non-volatile log buffer of the last 150 000 events
Standard	...	TCP/IP
IR illuminator	...	—
Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface 	...
LED illuminator	...	—
Video output	...	—
RS-485 interface	...	✓
Memory card slot	...	—
Alarm inputs / outputs	...	—
Audio	...	Speaker built-in
Network interface	...	10/100/1000 Mbps (RJ-45)
Network protocols	...	TCP/IP, ISUP, ISAPI

WEB Server	...	Built-in
Main features	<ul style="list-style-type: none"> • Metal housing • The MCX2D I/O expander included • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	...
ONVIF	...	—
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	port 8000
Operation temp	5 °C ... 40 °C	...
Permissible relative humidity	10 % ... 95 % (non-condensing)	...
Main features	...	<ul style="list-style-type: none"> • 4.3 " capacitive touch screen • Mechanical tamper protection • WDR - Wide Dynamic Range • AI detection : Face recognition • Configuration and management from the iVMS-4200 application • Port USB • Recording of information about Time&Attendance • Possibility to open the gate using a QR code • Door lock control output • Possibility to connect an exit button and a reed switch to control the door status

Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	12 V DC / 2 A (power adapter included)
Power consumption	...	≤ 24 W
Housing	...	Metal
Color	...	Black / Silver
"Index of Protection"	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	4.25 kg	0.31 kg
Dimensions	405 x 365 x 123 mm	173 x 83 x 23 mm (without bracket)
Supported languages	...	English, German, French, Polish, Czech, Hungarian, Bulgarian, Serbian, Slovenian, Albanian
Manufacturer / Brand	ROGER	Hikvision
SAP Code	...	302917454
Guarantee	3 years	3 years