



| | IP CAMERA IPC2125SB-ADF28KMC-I0-BLACK Tri-Guard - 5 Mpx 2.8 mm UNIVIEW | IP CAMERA IPC2124LE-ADF28KMC-WL ColorHunter - 4 Mpx 2.8 mm UNIVIEW |
|-----------------------------------|---|---|
| |  |  |
| | 1120.00 PLN 1120.00 PLN | 710.00 PLN 710.00 PLN |
| Standard | TCP/IP | TCP/IP |
| Sensor | 1/2.7 " Progressive Scan CMOS | 1/3 " Progressive Scan CMOS |
| Matrix size | 5 Mpx | 4 Mpx |
| Resolution | 2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p | 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p |
| Lens | 2.8 mm | 2.8 mm |
| View angle | <ul style="list-style-type: none"> • 113 ° (manufacturer data) • 104 ° (our tests result) | <ul style="list-style-type: none"> • 113 ° (manufacturer data) • 97 ° (our tests result) |
| Range of IR illumination | 30 m | 30 m |
| White light LED illuminator range | 30 m | 30 m |
| S/N ratio | > 56 dB | > 52 dB |
| RS-485 interface | ... | — |
| Memory card slot | Micro SD memory cards up to 256GB support (possible local recording) | Micro SD memory cards up to 128GB support (possible local recording) |
| Image compression method | Ultra 265 / H.265 / H.264 / MJPEG | Ultra 265 / H.265 / H.264 / MJPEG |
| Alarm inputs / outputs | — | — |
| Audio | <ul style="list-style-type: none"> • Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support | <ul style="list-style-type: none"> • Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support |
| Main stream frame rate | 25 fps @ 5 Mpx | 25 fps @ 4 Mpx |
| Network interface | 10/100 Base-T (RJ-45) | 10/100 Base-T (RJ-45) |
| Network protocols | IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, QoS, SSH | IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, SSL / TLS |
| WEB Server | Built-in | Built-in |
| Max. number of on-line users | 32 | 32 |
| ONVIF | ✓ | ✓ |
| Mobile phones support | Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView | Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView |

| | | |
|-------------------------------|--|--|
| Default IP address | DHCP or 192.168.1.13 | DHCP or 192.168.1.13 |
| Default admin user / password | admin / 123456 | admin / 123456 |
| Web browser access ports | 80, 554 | 80, 554 |
| PC client access ports | Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation | Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation |
| Mobile client access ports | 80 | 80 |
| Port ONVIF | 80 | 80 |
| RTSP URL | rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream | rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream |
| Main features | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • Active deterrence function - Light and sound alarm • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Active deterrence function - Intelligent alarm linked to turning on white light and loudspeaker • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, face detection, people counting, crowd gathering estimation | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire) (human silhouette) |
| Power supply | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 960 mA | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 750 mA |
| Power consumption | ≤ 11.5 W | ≤ 9 W |
| Housing | Compact, Metal + Plastic | Compact, Metal + Plastic |

| | | |
|-----------------------|--|--|
| Color | Black | White |
| "Index of Protection" | IP67 | IP67 |
| Vandal-proof | — | — |
| Operation temp | -30 °C ... 60 °C | -30 °C ... 60 °C |
| Weight | 0.42 kg | 0.41 kg |
| Dimensions | 191 75 x 74 mm | 191 75 x 74 mm |
| Supported languages | Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian | Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian |
| Manufacturer / Brand | UNIVIEW | UNIVIEW |
| Guarantee | 3 years | 3 years |