



	<a href="#">AHD, HD-CVI, HD-TVI CAMERA APTI-H50F2-28W 2Mpx / 5Mpx 2.8 mm</a>	<a href="#">SINGLE-MODE PATCHCORD PC-2SC/2ST 1 m</a>
		
	757.34 CZK 757.34 CZK	113.06 CZK 113.06 CZK
Standard	AHD, HD-CVI, HD-TVI	...
Connector type	...	SC/UPC <-> ST/UPC, Duplex
Sensor	1/2.7 " Progressive Scan CMOS	...
Matrix size	5 Mpx	...
Fiber optic type	...	9 / 125 μm
Total insertion loss	...	≤ 0.20 dB
Main features	...	<ul style="list-style-type: none"> <li>• Made according to the requirements: G.652 D</li> <li>• LSZH (Low Smoke Zero Halogen) coating - means small amount of toxic gases emitted during combustion</li> <li>• Cable diameter : 2.0 mm</li> </ul>
Length	...	1 m
Resolution	<ul style="list-style-type: none"> <li>• 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps ;</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps,</li> <li>• 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps</li> </ul>	...
Range of IR illumination	20 m	...
IR illuminator power adjustment	Automatic	...
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> <li>• 95 ° (manufacturer data)</li> <li>• 104 ° (our tests result)</li> </ul>	...
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	...

Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Day/night mode</li> </ul>	...
OSD menu	✓	...
Power supply	12 V DC / 310 mA	...
Power consumption	≤ 3.7 W	...
Housing	Dome - Metal + Plastic	...
Color	White	...
"Index of Protection"	—	...
Vandal-proof	—	...
Supported languages	Polish, English, French, Spanish, Korean, Portuguese, Russian, Italian	...
Operation temp	-10 °C ... 60 °C	...
Weight	0.30 kg	...
Dimensions	Ø 120 x 99 mm	...
Manufacturer / Brand	APTI	...
Guarantee	2 years	2 years