



	<a href="#">COAXIAL CABLE TRISSET-11PE/ZEL</a>	<a href="#">DIGITAL UNIPHONE MP800/3.5 ACO</a>
		
	4.76 PLN 4.76 PLN	595.41 PLN 595.41 PLN
Compatibility	...	ACO CDNP, Inspiro, Familio P/PV
In section	<b>100 m . Price for 1m when buying a whole roll</b>	...
Coaxial cable	TRISSET	...
Installation type	...	PV digital system, UTP cat. 5e, 6
LCD display	...	3.5 "
Inner conductor	Ø 1.63 mm Cu Wire	...
Dielectric	Ø 7.11 mm (physical foam)	...
Shield	Al/PET/Al - 9 µm / 23 µm / 9 µm	...
Braid	86 % Al wire	...
Outer coating	Ø 10.2 mm PE + gel	...
Coating color	Black	...
Resistance of the inner conductor for DC current	8.3 Ω/km	...
Capacity	52 pF/m	...
Dielectric resistance	2000 MΩ/km	...
Shortening wave coefficient	84 %	...
Impedance	75 Ω	...
Main features	<ul style="list-style-type: none"> <li>• low attenuation</li> <li>• perfect matched</li> <li>• high screening efficiency</li> <li>• PE coating</li> </ul>	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Image preview without active connection,</li> <li>• 7-level volume adjustment,</li> <li>• Relay output : 1 pcs,</li> <li>• Number of ring-tones : 4,</li> <li>• DIP SWITCH for configuration and addressing,</li> <li>• Connector for an additional bell button,</li> <li>• Full call privacy (no possibility of eavesdropping on the call),</li> <li>• Illuminated buttons</li> </ul>
Power supply	...	15 V DC, 280 mA (power adapter not included)
Housing	...	Plastic
Color	...	White

Operation temp	...	10 °C ... 40 °C
Weight	...	0.250 kg
Dimensions	...	198 x 82 x 27 mm
Manufacturer / Brand	...	ACO
Cable attenuation at 100m section	2.5 dB @ 47 MHz 4.1 dB @ 88 MHz 5.6 dB @ 174 MHz 6.5 dB @ 230 MHz 9.3 dB @ 470 MHz 13.2 dB @ 862 MHz 13.9 dB @ 950 MHz 21.0 dB @ 2150 MHz 21.6 dB @ 2400 MHz	...
Guarantee	2 years	2 years