



	<a href="#">IP CAMERA DS-2CD6425G1-30(2.8MM)(8M) - 1080p 2.8 mm</a> <a href="#">Hikvision</a>	<a href="#">USB WEB CAMERA</a> <a href="#">HQ-730IPC - 1080p 3.6 mm</a>
		
	2300.00 PLN 2300.00 PLN	59.00 PLN 59.00 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/2.8 " Progressive Scan CMOS	1/2.9 " Progressive Scan CMOS
Matrix size	2.1 Mpx	2.1 Mpx
Scanning system	...	Progressive
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p 640 x 480 - VGA , 640 x 360 , 320 x 240 - QVGA	1920 x 1080 - 1080p , 1920 x 720 , 640 x 360
Interface	...	USB 2.0
Image compression method	H.265+ / H.265 / H.264 / MJPEG	H.264 / MJPEG
Lens	2.8 mm, F2.0	3.6 mm
Main stream frame rate	25 fps @ 1080p	25 fps @ 1080p
View angle	• 108 ° (manufacturer data) • 104 ° (our tests result)	85 °
Min. illumination	0.002 Lux @ F1.2, AGC	...
Housing	...	Compact - Plastic
Audio	<ul style="list-style-type: none"> <li>• Audio input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> <li>• Noise reduction</li> </ul>	Microphone built-in - Noise and echo reduction
Color	...	Black
RS-485 interface	Half Duplex, Pelco-P, Pelco-D, Hikvision	...
RS-232 interface	—	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	—
Alarm inputs / outputs	1 / 1	—
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, UDP, Bonjour, SSL / TLS	UVC, UVA
ONVIF	✓	...
WEB Server	✓	...
Max. number of on-line users	15	...

Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/	...
Main features	<ul style="list-style-type: none"> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• Configurable Privacy Zones</li> <li>• Day/night mode - manual/auto</li> <li>• AGC - Automatic Gain Control</li> <li>• Configurable: brightness, contrast, saturation</li> <li>• Sharpness - sharper image outlines</li> <li>• Motion Detection - Split the screen into zones : 22 x 18</li> <li>• IVS analysis - crossing the line (tripwire), intrusion, abandoned/missing object, scene changing, entering the marked area, leaving the marked area, Lens focus loss detection, loitering detection, detection of people gathering, fast moving, illegal parking</li> </ul>	Easy installation - Plug&Play USB device type
Power supply	• 12 V DC / 250 mA, • PoE (802.3af)	5 V DC / 160 mA - Port USB
Power consumption	max. 3 W @ 12 V max. 3.65 W @ PoE	< 0.8 W
Operation temp	-30 °C ... 60 °C	-20 °C ... 60 °C
Weight	0.09 kg - Network module 0.08 kg - Camera	0.12 kg
Dimensions	78 x 70 x 26 mm - Network module Ø 26 x 52 mm - Camera	71 x 54 x 45 mm
Length of the cable	8 m	1.6 m
Supported languages	English, Bulgarian, Czech, Estonian, French, Spanish, Lithuanian, German, Portuguese, Russian, Slovak, Turkish, Hungarian, Vietnamese	...
SAP Code	311318354	...
Manufacturer / Brand	Hikvision	...

Guarantee	3 years	2 years
-----------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00