

	AHD, HD-CVI, HD-TVI, PAL CAMERA DH-HAC-HFW1200TLP-A - 1080p 3.6 mm DAHUA	SWITCH POE GTS-A1-06-42 4-PORT	ACCESS CONTROLLER WITH FACE RECOGNITION DS-K1T341AM-S - 720p Hikvision	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT APTI-AI71FRTD 4.5 mm - 1080p	QUICK-CONNECTOR S-55*P100
					
	202.00 PLN 202.00 PLN	248.00 PLN 248.00 PLN	1999.00 PLN 1999.00 PLN	240.00 PLN 240.00 PLN	71.50 PLN 71.50 PLN
LAN ports	...	6 x RJ45 (4 x PoE (802.3at))
In package	100 pcs The price for package
Scanning system	Progressive	...
Connector type	Ø 2.1 / 5.5 mm Straight plug
Cards support	13.56 MHz S50
Optical zoom	—	...
Wire mounting	Cable terminals
Application	Electric cable
Material	PET
Sensor	1/2.7 " CMOS	...	CMOS	1/2.8 " SONY Starvis™ Back-illuminated CMOS 1/5 " GC2145	...
Matrix size	2.1 Mpx	...	2 Mpx	2.1 Mpx 2 Mpx	...
Memory	<ul style="list-style-type: none"> • Memory of 1500 face templates • Memory of 1500 RFID cards • Non-volatile log buffer of the last 150 000 events
Management	...	—
Example of application	<ul style="list-style-type: none"> • OMY-2X0.75 • K-60 • YAP
Pixel pitch	1.75 µm	...
Lens	3.6 mm	4.5 mm 2.4 mm	...
IR illuminator	—
LED diodes	...	Power, LAN, PoE
LED illuminator	—
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	...	1280 x 720 - 720p	1920 x 1080 - 1080p 800 x 600 - 0.48 Mpx	...
View angle	<ul style="list-style-type: none"> • 88 ° (manufacturer data) • 86 ° (our tests result) 	68 ° 70 °	...
Transmission speed	...	10 / 100 Mbps : 2 Port LAN + 4 LAN & PoE ports
Standard	AHD, HD-CVI, HD-TVI, CVBS	...	TCP/IP	TCP/IP	...
Range of IR illumination	80 m	5 m	...
IR illuminator power adjustment	Automatic
Maximal output power	...	30 W / port PoE
White light LED illuminator range	5 m	...
Maximal total power	...	60 W
Temperature measurement	✓	...
MAC addresses table	...	1k

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Temperature measurement range	35 °C ... 42 °C	...
Accuracy of temperature measurement	± 0.3 °C	...
Main features	...	• RESET button • 2 x Port Uplink • IEEE 802.1Q VLAN - Turning by switch	• Very easy and quick assembly
Certificates	...	CE
Face recognition distance	0.3 m ... 1.5 m	0.5 m ... 2.3 m (max 30 000 faces in the database)	...
S/N ratio	> 65 dB
OSD menu	✓
Temperature measurement distance	0.5 m ... 1.3 m optimal distance : 0.75 m	...
Internal memory	Support storage of 25 000 records	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...	—	—	...
RS-485 interface	✓	✓	...
Wiegand interface	✓	...
Memory card slot	—	—	...
Alarm inputs / outputs	—	0 / 2 (bolt control, signaling of exceeding the temperature)	...
Relay output	NO, NC	...
Audio	Microphone built-in, HD-CVI only	...	Speaker built-in	Speaker built-in	...
Network interface	10/100/1000 Mbps (RJ-45)	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, ISUP, ISAPI	IPv4, HTTP, HTTPS, TCP/IP	...
WEB Server	Built-in	Built-in	...
Max. number of on-line users	20	...
ONVIF	—	—	...
RS-485	✓	...
Default IP address	192.168.1.64	DHCP / 192.168.1.88	...
Default admin user / password	admin / - The administrator password should be set at the first start	admin / 12345	...
Web browser access ports	80	7080	...
PC client access ports	port 8000	7080	...
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Mirror - Mirror image • Auto White Balance 	...	<ul style="list-style-type: none"> • 4.3 " capacitive touch screen • Mechanical tamper protection • WDR - Wide Dynamic Range • AI detection : Face recognition • Configuration and management from the iVMS-4200 application • Port USB • Recording of information about Time&Attendance • Possibility to open the gate using a QR code • Door lock control output • Possibility to connect an exit button and a reed switch to control the door status 	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera and the result of temperature measurement - 1024 x 600 px • Day/Night mode (color/b&w/auto) • RESET button • Wiegand 26 • Relay output operating modes: access control or notification of an exception 	...

Power supply	12 V DC / 440 mA	48 ... 56 V DC / 1.25 A (2.5/5.5mm socket) - Power adapter included	12 V DC / 2 A (power adapter included)	12 V DC	...
Power consumption	≤ 5.3 W	...	≤ 24 W	≤ 12 W	...
Housing	Compact, Plastic / Metal	...	Metal	Compact - Metal	...
Color	White	...	Black / Silver	Silver	...
SAP Code	302917454
"Index of Protection"	IP67	...	—	IP66	...
Operation temp	-40 °C ... 60 °C	...	-30 °C ... 60 °C	15 °C ... 25 °C - temperature measurement only in closed rooms (stabilized temperature)	...
Weight	0.28 kg	0.37 kg	0.31 kg	0.76 kg	0.006 kg
Dimensions	80 x 75 x 199 mm	160 x 95 x 27 mm	173 x 83 x 23 mm (without bracket)	112 x 220 x 41 mm (with bracket)	37 x 14 x 12 mm
Length of the cable	64 cm	...
Supported languages	English, German, French, Polish, Czech, Hungarian, Bulgarian, Serbian, Slovenian, Albanian	Polish, English, French, Spanish, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	DAHUA	...	Hikvision	APTI	...
Guarantee	3 years	2 years	3 years	3 years	2 years