



	ACCESS CONTROLLER WITH FACE RECOGNITION DS-K1T341AM-S - 720p Hikvision	ACCESS CONTROLLER MODULE MC16-PAC-ST-3 ROGER
		
	1999.00 PLN 1999.00 PLN	1750.00 PLN 1750.00 PLN
Sensor	CMOS	...
Number of served transitions	...	3 (two-way)
Number of supported readers	...	12
Matrix size	2 Mpx	...
Number of users	...	unlimited (purchase of the appropriate license required)
Resolution	1280 x 720 - 720p	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Cards support	13.56 MHz S50	...
Buffer memory	...	8 000 000 events buffer
Number of access zones	...	6
Face recognition distance	0.3 m ... 1.5 m	...
Number of alarm zones	...	6
Battery backup support	...	12 V / 7 Ah
Memory	<ul style="list-style-type: none"> • Memory of 1500 face templates • Memory of 1500 RFID cards • Non-volatile log buffer of the last 150 000 events 	...
Standard	TCP/IP	...
IR illuminator	—	...
Communication	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface
LED illuminator	—	...
Video output	—	...
RS-485 interface	✓	...
Memory card slot	—	...
Alarm inputs / outputs	—	...
Audio	Speaker built-in	...
Network interface	10/100/1000 Mbps (RJ-45)	...

Main features	...	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128
Network protocols	TCP/IP, ISUP, ISAPI	...
WEB Server	Built-in	...
ONVIF	—	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	port 8000	...
Operation temp	...	5 °C ... 40 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)
Main features	<ul style="list-style-type: none"> • 4.3 " capacitive touch screen • Mechanical tamper protection • WDR - Wide Dynamic Range • AI detection : Face recognition • Configuration and management from the iVMS-4200 application • Port USB • Recording of information about Time&Attendance • Possibility to open the gate using a QR code • Door lock control output • Possibility to connect an exit button and a reed switch to control the door status 	...

Power supply	12 V DC / 2 A (power adapter included)	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Power consumption	≤ 24 W	...
Housing	Metal	...
Color	Black / Silver	...
"Index of Protection"	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.31 kg	0.14 kg
Dimensions	173 x 83 x 23 mm (without bracket)	175 x 72 x 30 mm
Supported languages	English, German, French, Polish, Czech, Hungarian, Bulgarian, Serbian, Slovenian, Albanian	...
Manufacturer / Brand	Hikvision	ROGER
SAP Code	302917454	...
Guarantee	3 years	3 years