



	<a href="#">IP CAMERA DS-2CD2083G2-IU(2.8MM)(BLACK) ACUSENSE - 8.3 Mpx Hikvision</a>	<a href="#">IP CAMERA DS-2CD2083G2-I(2.8MM) ACUSENSE - 8.3 Mpx Hikvision</a>
		
	1363.00 PLN 1363.00 PLN	1296.00 PLN 1296.00 PLN
Standard	TCP/IP	TCP/IP
Sensor	1/2.8 " Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS
Matrix size	8.3 Mpx	8.3 Mpx
Resolution	3840 x 2160 - 8.3 Mpx , 3200 x 1800 - 5 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx , 3200 x 1800 - 5 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	2.8 mm	2.8 mm
View angle	107 °	107 °
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination	40 m	40 m
Alarm inputs / outputs	—	—
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Audio detection</li> </ul>	—
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	Micro SD memory cards up to 512GB support (possible local recording)
Main stream frame rate	20 fps @ 8.3 Mpx 25 fps @ 6 Mpx	25 fps @ 8.3 Mpx
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
WEB Server	Built-in	Built-in
Max. number of on-line users	6	6
ONVIF	✓	✓
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>
Default IP address	192.168.1.64	192.168.1.64
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Web browser access ports	80	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000	8000
Port ONVIF	80	80
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>
RS-485 interface	—	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> <li>• Camera from AcuSense series</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• ICR - Movable InfraRed filter</li> <li>• Configurable Privacy Zones</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, face detection</li> </ul>	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• ICR - Movable InfraRed filter</li> <li>• Configurable Privacy Zones</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, face detection</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 500 mA</li> </ul>	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 500 mA</li> </ul>
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 7.2 W @ PoE (802.3af)</li> <li>• ≤ 6 W @ 12 V DC</li> </ul>	<ul style="list-style-type: none"> <li>• ≤ 7.2 W @ PoE (802.3af)</li> <li>• ≤ 6 W @ 12 V DC</li> </ul>
Housing	Compact, Metal	Compact, Metal
Color	Black	White
"Index of Protection"	IP67	IP67
Operation temp	-30 °C ... 60 °C	-30 °C ... 60 °C
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian
Weight	0.49 kg	0.5 kg
Dimensions	Ø 70 x 162 mm	Ø 70 x 162 mm
Manufacturer / Brand	Hikvision	Hikvision
SAP Code	311316475	311316039
Guarantee	3 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00