



	ACCESS POINT MAP-2ND mAP, 2.4 GHz 300 Mbps MIKROTIK	INTERMEDIATE SWITCH DW7.01/11-SIMON54 250 V 10 A
		
	210.68 PLN 210.68 PLN	26.30 PLN 26.30 PLN
Frequency range	2.4 GHz	...
Processor	Qualcomm Atheros AR9531 650 MHz	...
Device type	...	Intermediate Switch (bistable)
Rated voltage	...	250 V AC
Rated current	...	10 A (inductive load)
Antenna type	2 x 2 MIMO Omnidirectional antenna , Dual-chain - embedded 1.2 dBi	...
Standards	IEEE 802.11 b/g/n	...
Connectors type	...	Quick-connector
Baud rates	300 Mbps	...
LAN ports	2 x 10 / 100 Mbps LAN	...
Application	...	Flush-mounted, Simon 54 product series, for Nature, Premium frames
Backlight	...	—
Assembly	...	Claw or screw mounting
LED indicators	Power, Operation mode, WiFi, User, PoE OUT, 2 x Ethernet	...
"Index of Protection"	...	IP20 / IP44 (using frame seal)
Housing	...	Non-halogen plastic, PC
Color	...	White (RAL 9003)
Receiver sensitivity	2.4 GHz : • 1M : -96 dBm • 11M : -89 dBm • 6M : -93 dBm • 54M : -74 dBm • MCS0 : -93 dBm • MCS7 : -71 dBm	...
Transmitter power	max. 22 dBm	...
DHCP server	✓	...

Firmware update	✓	...
Operating system	MikroTik RouterOS	...
Management interface	Web browser, MikroTik application	...
Default IP address	192.168.88.1	...
Operation modes	<ul style="list-style-type: none"> • Access Point, • Station 	...
Power supply	<ul style="list-style-type: none"> • 8 ... 57 V DC - 24 V DC / 0.8 A (power adapter included) • 10 ... 57 V DC - Passive PoE, PoE (802.3af/at) • 5 V DC - Micro USB-B socket 	...
Power consumption	max. 5 W	...
Main features	<ul style="list-style-type: none"> • Dual-chain • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Built-in 2-port switch • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Port USB 2.0 - Possibility to connect 3G/4G modem, Power connector • PoE IN : PoE 802.3af/at / PASSIVE - port ETH1 • PoE OUT : Passive PoE - port ETH2 • Voltage control • Mode button • RESET button • USB A / micro USB B cable included 	Pictogram
Operation temp	-20 °C ... 70 °C	...
Weight	0.068 kg	0.06 kg
Dimensions	68 x 68 x 19 mm	<ul style="list-style-type: none"> • 75 x 75 x 41 mm • 26 mm - mounting depth
Manufacturer / Brand	MikroTik	KONTAKT Simon
Guarantee	2 years	6 years